

**Fecal Coliform Bacteria
Total Maximum Daily Load for
Shellfish Monitoring Station
in Russell Creek
Shellfish Management Area 12B
HUCs 030502060405, 030502060307, 030502060308**



**SC DEPARTMENT of
ENVIRONMENTAL
SERVICES**

Bureau of Water

Banu Varlik

USEPA Approval Date: 8/20/2025

Technical Report Number: 005-2025

Abstract

§303(d) of the CWA and USEPA's *Water Quality Planning and Management Regulations* (40 CFR - Protection of Environment 2017) require states to develop TMDLs for water bodies that are included on the §303(d) list of impaired waters. A TMDL is the maximum amount of pollutant a waterbody can assimilate while meeting WQS for the pollutant of concern. All TMDLs include a WLA for any NPDES permitted dischargers, an LA for all nonpoint sources, and an explicit and/or implicit MOS. This technical report describes the development of FC TMDL for impaired shellfish monitoring station 12B-43A in Russell Creek, Charleston County, SC. This station has been included in SC's draft 2024 §303(d) list of impaired waters for exceeding FC WQS for SFH use and have been prioritized and accepted by EPA as metrics in the CWA §303(d) program performance measures.

SCDOT is an NPDES permitted TS4. For SCDOT, compliance with terms and conditions of its NPDES TS4 permit is effective implementation of the WLA to the MEP. Charleston County is also an NPDES permitted MS4 in this watershed. Charleston County has been allocated WLAs.

Table Ab1. TMDL for Russell Creek. TMDL is expressed as the mpn/100 mL and mpn/day, and allocations are expressed as % reductions.

Station	Existing Conc. (mpn/100mL)	TMDL Conc. ¹ (mpn/100mL)	TMDL Load ² (WLA+LA+MOS) (mpn/day)	Implementation Targets ⁶			
				Continuous Sources ³ (mpn/100mL)	Intermittent MS4 ⁵ (%)	Intermittent TS4 SCDOT (%) ^{4, 5}	Nonpoint Sources (%)
12B-43A	88.3	43	1.68E+12	See Note Below	53.7%	53.7% ^{4, 5}	53.7%

Table Notes:

1. TMDL = SFH WQS for SSM not to exceed 43 mpn/100 mL FC.
2. TMDL at average flow conditions calculated using estimated average tidal flow at the WQ station. See Appendix B for example calculation.
3. WLA is expressed as a daily maximum of 43 mpn/100 mL FC. There are no continuous dischargers at this time. Future continuous discharges are required to meet the WQS for the pollutant of concern. Loadings to meet the WQS are developed based on the permitted flow and an allowable permitted maximum concentration of 43 mpn/100mL FC.
4. By implementing the BMPs that are prescribed in either the SCDOT annual SWMP or the SCDOT NPDES TS4 permit to address bacteria, the SCDOT will comply with this TMDL and its applicable WLA to the MEP as required by its NPDES TS4 permit.
5. Percent reduction applies to all NPDES permitted stormwater discharges, including current and future TS4, MS4s, construction, and industrial discharges covered under permits numbered SCS & SCR. Stormwater discharges are expressed as a percentage reduction due to the uncertain nature of stormwater discharge volumes and recurrence intervals. Stormwater discharges are required to meet percentage reduction or the existing instream standard for the pollutant of concern in accordance with their NPDES Permit.
6. Refer to section 6.0 for the derivation of implementation targets.

Contents

Abstract.....	ii
List of Abbreviations and Symbols	vi
1.0 Introduction	1
1.1 Background	1
1.2 Watershed Description	4
1.3 Land use	6
1.4 Water Quality Standard	9
2.0 Water Quality Assessment	9
3.0 Source Assessment	10
3.1 Point Sources	11
3.1.1 Continuous Point Sources	11
3.1.2 Intermittent Point Sources – TS4 and MS4s.....	11
3.2 Nonpoint Sources.....	14
3.2.1 Wildlife	15
3.2.2 Agriculture	15
3.2.3 Land Application of Industrial, Domestic Sludge or Treated Wastewater ..	17
3.2.4 Leaking Sanitary Sewer and Illicit Discharges.....	18
3.2.5 Failing Septic Systems.....	18
3.2.6 Stormwater Runoff.....	19
3.2.7 Marinas, Boating Activities, and Structures	19
4.0 Cumulative Probability Method.....	19
5.0 Development of the TMDL.....	22
5.1 Critical Conditions	22
5.2 Wasteload Allocation	22
5.2.1 Continuous Point Sources	22
5.2.2 Intermittent Point Sources	23
5.3 Load Allocation	23
5.4 Existing Load	24
5.5 Margin of Safety.....	24

5.6 Calculation of the TMDL	24
5.7 Reasonable Assurance.....	24
6.0 Implementation.....	27
6.1 Continuous Sources	27
6.1 Intermittent Point Sources – MS4s.....	27
6.2 Nonpoint Sources.....	28
7.0 References.....	28
Appendix A – Data Used for Calculation of the TMDL	30
Appendix B - The Method Used for Calculate the Daily Load.....	31

Figures

Figure 1. Locations of shellfish management area 12B, Russell Creek TMDL watershed in Charleston County, SC.....	3
Figure 2. Russell Creek TMDL watershed in SFMA 12B, impaired and boundary shellfish monitoring stations, and shellfish harvesting classifications.....	5
Figure 3. TMDL stations drainage areas.	6
Figure 4. Land uses of the TMDL watersheds based on 2021 NLCD.	8
Figure 5. SCDOT TS4 and Charleston County MS4 are designated entities within the TMDL watershed.....	13
Figure 6. Cumulative probability plot for station 12B-43A.	21

Tables

Table 1. Russell Creek shellfish monitoring stations and their location descriptions..	4
Table 2. 2021 NLCD land uses of 12B-43A and 12B-43.	7
Table 3. Data summaries of TMDL stations.	10
Table 4. Estimated bacteria contributions from cattle and calves in the TMDL watershed.....	16
Table 5. Estimated bacteria contributions from horses and ponies in the TMDL watershed.....	17
Table 6. Single sample maximum and geometric mean percent reduction comparisons.....	21
Table 7. TMDL for Russell Creek. TMDL is expressed as the mpn/100 mL and mpn/day, and allocations are expressed as % reductions.	26
Table 8. Default velocities to be used in the absence of site-specific data.....	31

List of Abbreviations and Symbols

Abbreviation/ Symbol	Definition
ac	Acre
AVMA	American Veterinary Medical Association
BMP	Best Management Practices
CAFO	Confined Animal Feeding Operations
CFR	Code of Federal Regulations
cfu	Colony forming units
CWA	Clean Water Act
DA	Drainage Area
FC	Fecal Coliform
GIS	Geographic Information System
HUC	Hydrologic Unit Code
ISSC	Interstate Shellfish Sanitation Conference
LA	Load Allocation
MEP	Maximum Extent Practicable
MOS	Margin of Safety
MPN	Most Probable Number
MS4	Municipal Separate Storm Sewer System
MSD	Marine Sanitation Device
NLCD	National Land Cover Database
NOAA	National Oceanic and Atmospheric Administration
NPDES	National Pollution Discharge Elimination System
NSSP	National Shellfish Sanitation Program
ORW	Outstanding Resource Waters
R	Regulation
SA	Recreational Salt Waters
SB	Recreational Salt Waters
SC	South Carolina
SCDES	South Carolina Department of Environmental Services
SCDHEC	South Carolina Department of Health and Environmental Control
SCDNR	South Carolina Department of Natural Resources
SCDOT	South Carolina Department of Transportation
SFH	Shellfish Harvesting
SFMA	Shellfish Harvesting Management Area

SRS	Systematic Random Sampling
SSM	Single Sample Maximum
SSO	Sanitary Sewer Overflow
SWMP	Stormwater Management Plan
SWPPP	Stormwater Pollution Prevention Plan
TMDL	Total Maximum Daily Load
TS4	Transportation Separate Storm Sewer System
USDA	United States Department of Agriculture
USEPA	United States Environmental Protection Agency
USFDA	United States Food and Drug Administration
USGS	United States Geological Survey
WLA	Wasteload Allocation
WQ	Water Quality
WQM	Water Quality Management
WQS	Water Quality Standards
WWTP	Waste Water Treatment Plant
mi ²	Square Mile
n	Sample Size
%	Percent
§	Section
Σ	Sum, Total
mL	milliliter

1.0 Introduction

1.1 Background

The federal CWA requires each state to assess its waters, develop monitoring strategies, and establish WQS for various types and uses of water bodies. Furthermore, the CWA mandates states to review the monitoring results every two years to ensure compliance with the established WQS. If monitoring indicates that the WQS are not being met, the states are required to list the impaired bodies under §303(d) of the CWA. These listed sites are then assigned a priority ranking for restoration efforts, and the impairments are addressed through the implementation of TMDLs, as outlined in 40 CFR Part 130, based on their respective ranks (40 CFR - Protection of Environment 2017).

A TMDL is one part of a regulatory framework used to manage and control pollutant levels in water bodies that are impaired by pollutants. It establishes the maximum amount of a specific pollutant that a water body can receive from all sources, continuous point sources, intermittent point sources, and nonpoint sources, while still meeting WQS. The TMDL process includes estimating pollutant contributions from all sources, linking pollutant sources to their impacts on water quality, allocation of pollutant contributions to each source, and establishment of control mechanisms to achieve WQS.

A TMDL is comprised of the sum of individual WLAs (ΣWLA) for continuous and intermittent point sources, and sum of LAs (ΣLA) for nonpoint sources. In addition, the TMDLs include an MOS, either implicit or explicit, which is a buffer or safety factor included in the TMDL to account for uncertainties in the relationship between pollutant loads and water quality. Conceptually, this definition is represented by the equation:

$$TMDL = \Sigma WLA + \Sigma LA + MOS$$

This TMDL document is a detailed analysis describing the development of FC bacteria TMDL for one shellfish monitoring station located Russel Creek in SFMA 12B, in Charleston County, SC. Shellfish monitoring station 12B-43A has exceeded the shellfish harvesting WQS for “approved” classification and has been included in SC’s draft 2024 §303(d) list of impaired waters. Station 12B-43 is the downstream boundary for the impaired station, upstream of which is restricted for shellfish harvesting. The

impaired station has been prioritized and accepted by the USEPA as metrics in the CWA §303(d) program performance measures.

In SC, oysters and clams are the two species of bivalve molluscan shellfish that are harvested commercially, recreationally, and utilized for aquaculture. These two species are Eastern or American oyster, *Crassostrea virginica*, and hard clam or Northern quahog, *Mercenaria mercenaria*. Both species are native to the North American Atlantic and Gulf coasts and have economic importance. Oysters in SC cluster together to form oyster beds and oyster reefs. These formations stabilize shorelines from erosion, provide nursery grounds as well as protection for other marine species. In South Carolina, 95% of oyster reefs are intertidal, meaning they are exposed during low tide and submerged during high tide.

Both oysters and clams are filter feeders, meaning they filter water for algae as a nutrient source. In brackish and saltwaters, there are naturally occurring bacteria and viruses. Also, there are other sources for bacteria and viruses to enter these waters as a result of human activities, some examples are agricultural runoff, malfunctioning septic systems, pet waste, sanitary sewer overflows, and stormwater runoff. An adult oyster can filter approximately 50 gallons of water a day, while an adult clam can filter approximately 24 gallons a day. These filter feeders can concentrate naturally occurring bacteria, such as pathogenic bacteria *Vibrio vulnificus* and *Vibrio parahaemolyticus*, and viruses that are in the water as well as those resulting from human-related activities.

The NSSP is the federal and state cooperative program recognized by both the USFDA and the ISSC. States have agreed, through participation in NSSP and membership in the ISSC, to enforce the Model Ordinance (USFDA 2021). The Model Ordinance supplies states with standards as well as administrative practices required for the sanitary control of shellfish produced and sold for human consumption.

The FC group of bacteria is usually not pathogenic, and they are used as indicator organisms. As an indicator, they may indicate the presence of other pathogenic bacteria. In the NSSP Model Ordinance (USFDA 2021) and in SC R. 61-47 Shellfish (SCDHEC 2017), the WQS for SFH with an “approved” classification is “...the geometric mean fecal coliform MPN shall not exceed fourteen per one hundred milliliters, nor shall the estimated ninetieth percentile exceed an MPN of forty three per one hundred milliliters (per five tube decimal dilution)”. Shellfish R. 61-47 was promulgated by the

statutory authority under S.C. Code Section 44-1-140. This regulation adopted the shellfish FC WQS as set forth in the NSSP Model Ordinance.




Figure 1. Locations of shellfish management area 12B, Russell Creek TMDL watershed in Charleston County, SC.

1.2 Watershed Description

Russell Creek is tidal estuary tributary to North Edisto River and is located on Edisto Island, southwest of the City of Charleston in Charleston County, SC. The creek is encompassed within SFMA 12B and 12-digit HUCs 030502060405, 030502060307, and 030502060308 (Figure 1, Figure 2). The DA for the TMDL WQM stations were delineated using USGS topographic maps and ArcGIS software. Russell Creek TMDL area has an approximate DA of 3.02 mi² (Figure 3).

Russell Creek is located within the Sea Islands/Coastal Marsh ecoregion, characterized by the state's lowest elevations. This dynamic environment is shaped by elements such as wind, ocean waves, and river flows. Dominant forest types in this ecoregion include slash pine, cabbage palmetto, red cedar, and live oaks. Marshes play a significant role and are primarily populated by plant species like saltgrass, rushes, and various cordgrasses. Notably, these marshes serve as essential nursery grounds for a wide range of aquatic species, including shrimp, fish, crabs, and various other organisms (Griffith, et al. 2002).

SCDES formerly known as SCDHEC, currently has two active shellfish monitoring stations, 12B-43A and 12B-43, in Russell Creek. Station 12B-43A does not meet the FC WQS for shellfish harvesting waters and is classified as “restricted” for shellfish harvesting. Per USFDA rules and regulations, station 12B-43 is the downstream boundary of the area restricted for shellfish harvesting (Figure 2) (Table 1). The TMDL watershed extends to but does not include the boundary station and the implementation targets in Table 7 apply to the entire watershed as shown in Figure 3 and Figure 5.

Table 1. Russell Creek shellfish monitoring stations and their location descriptions.

Station	Description
12B-43A	Russell Creek at Creek Farm Rd.
12B-43	Russell Creek at estuary entering Sunbelt Clam Farms




Figure 2. Russell Creek TMDL watershed in SFMA 12B, impaired and boundary shellfish monitoring stations, and shellfish harvesting classifications.




Figure 3. TMDL stations drainage areas.

1.3 Land use

Land uses of impaired stations were calculated using the 2021 NLCD (Dewitz 2023) (Figure 4). Land use characteristics for TMDL stations are summarized in Table 2.

Table 2. 2021 NLCD land uses of 12B-43A and 12B-43.

	12B-43A Area (ac)	12B-43A % of Area	12B-43 Area (ac)	12B-43 % of Area
Open Water	83.2	7.5	90.3	11.0
Developed	21.6	1.9	47.4	5.8
Barren	4.2	0.4	3.6	0.4
Forest	345.6	31.1	235.3	28.6
Pasture/Hay	128.1	11.5	40.5	4.9
Cultivated Crops	n/a	n/a	21.1	2.6
Forested Wetlands	213.5	19.2	90.5	11.0
Non-forested Wetlands	315.4	28.4	293.6	35.7
Total	1111.5	100.0	822.2	100.0




Figure 4. Land uses of the TMDL watersheds based on 2021 NLCD.

1.4 Water Quality Standard

Russell Creek is classified as SFH and ORW in SC R. 61-69 as (SCDHEC 2012).

As defined in SC R. 61-68 as (SCDHEC 2023):

“Shellfish harvesting waters (SFH) are tidal saltwaters protected for shellfish harvesting and uses listed in Class SA and Class SB. Suitable for primary and secondary contact recreation, crabbing, and fishing. Also suitable for the survival and propagation of a balanced indigenous aquatic community of marine fauna and flora.”

As defined in SC R. 61-68 as (SCDHEC 2023):

“Outstanding Resource Waters (ORW) are freshwaters or saltwaters which constitute an outstanding recreational or ecological resource or those freshwaters suitable as a source for drinking water supply purposes with treatment levels specified by the Department”.

FC WQS for SFH as defined in SC R. 61-68 as (SCDHEC 2023):

“Not to exceed an MPN fecal coliform geometric mean of 14/100 mL; nor shall more than ten percent (10%) of the samples exceed an MPN of 43/100 mL.”

2.0 Water Quality Assessment

The NSSP allows shellfish growing areas to be classified using either total or fecal coliform, and application of either standard to different water bodies within the state. There are also two sampling strategies for the application of the standards:

- a) Adverse pollution control,
- b) SRS (USFDA 2021).

SCDES Shellfish Program currently utilizes the SRS strategy within SFMA 12B instead of sampling under adverse pollution control conditions. To ensure random sampling, sampling dates are computer-generated before the beginning of each quarterly period. Due to shipping requirements and manpower constraints, samples are collected on Mondays, Tuesdays, or Wednesdays.

To comply with NSSP guidelines, a minimum of 30 samples are required to be collected and analyzed from each station during the three-year review period. For harvest classifications, samples are collected according to the SRS strategy outlined in NSSP Guidance document for 12 months between January 1st and December 31st, for three years. This allows for a maximum of 36 samples per station for three years yet

provides a six-sample “cushion” (above the NSSP required 30 minimum) for broken samples, lab error, breakdowns, etc. This also allows each annual report to meet the NSSP Triennial Review sampling criteria.

The determination for §303(d) listing purposes is based on assessing three consecutive years of data from a shellfish station. For instance, for the draft 2024 §303(d) list, shellfish data collected from 2020 - 2022 were used. Note that station 12B-43 meets the WQS and is the downstream boundary for the impaired station 12B-43A in accordance with NSSP (USFDA 2021) and R. 61-47 (SCDHEC 2017). Data summaries for TMDL stations are presented in Table 3.

In addition to bacteriological samples, surface water temperatures are measured using a hand-held, laboratory-quality calibrated thermometer. Salinities are measured in the laboratory using an automatic temperature compensated refractometer. Additional field data collected during samplings are ambient air temperature, wind direction, tidal stage, date, and time of sampling.

Table 3. Data summaries of TMDL stations.

Station	n	SSM WQS mpn/100mL	n Exceeding SSM WQS	% Exceeding SSM WQS	TMDL Data Period
12B-43A	36	43	7	19%	2020-2022
12B-43*	36	43	3	8%	2020-2022

* 12B-43 is the downstream boundary station for the restricted area and meets the FC WQS for shellfish harvesting use. Data included for informational purposes.

3.0 Source Assessment

Surface waters can be contaminated by various sources of pathogens, which can be categorized as point sources, and nonpoint sources. Efforts to control pollution from continuous point sources, such as WWTPs, have significantly reduced their impact through the implementation of technology-based controls. These point sources are regulated under the CWA and are required to obtain an NPDES permit. In SC, NPDES permits mandate that dischargers with a bacteria limit to meet the WQS at the discharge point (end of pipe). While dischargers, mostly domestic and municipal, can occasionally be sources of pathogens, if they are operating within their permit limits, they cannot be considered the cause of impairments. There are enforcement actions and mechanisms in place if these facilities fail to meet their permit requirements.

Regulated TS4, MS4, industrial, and construction site stormwater discharges are intermittent point sources. These intermittent sources are required to obtain discharge permits under the NPDES stormwater regulations. Each may be a source of pathogens. These sources are expected to meet the percentage reductions as prescribed in this TMDL document or the existing instream standard for the pollutant(s) of concern, to the MEP, through compliance with the terms and conditions of their NPDES permit.

Nonpoint sources of bacteria in tidal stream include various land-use practices such as agricultural activities, silviculture, urban and rural runoff, malfunctioning septic systems, sanitary sewer overflows, pet waste, wildlife, and poorly managed livestock operations. These activities can contribute to the presence of bacteria in surface water through runoff, leaching, and direct discharge.

3.1 Point Sources

Point sources refer to specific locations where NPDES permitted effluent is discharged into the environment from identifiable sources such as pipes, outfalls, or conveyance channels. These sources can be traced to a single location such as industrial, municipal, domestic WWTPs, and NPDES regulated stormwater discharges. Point sources are further divided into “continuous” and “intermittent”.

3.1.1 Continuous Point Sources

Industrial, municipal, and domestic WWTPs have the potential to harbor pathogenic bacteria if their effluent fails to meet the WQS at the discharge point, as defined by their NPDES permit. If these facilities are discharging wastewater that meets their permit limits, they are not contributing to a bacteria impairment. If any of these facilities fail to comply with their permit limits, enforcement actions and mechanisms are in place to address the situation.

Currently, there are no continuous point sources within the TMDL watersheds. Future NPDES dischargers to these creeks are required to comply with their permit limit for FC which will limit them to the WQS at the point of discharge.

3.1.2 Intermittent Point Sources – TS4 and MS4s

Intermittent point sources include all NPDES permitted stormwater discharges, including current and future TS4, MS4, construction, and industrial discharges covered

under permits numbered SCS and SCR and regulated under *SC Water Pollution Control Permits*: R.61-9 (SCDHEC 2023). All regulated TS4 and MS4 entities have the potential to contribute bacteria and other pathogen loadings to the TMDL watersheds and are subject to the WLA for intermittent point sources.

The presence of developed land in a watershed leads to increased runoff from these areas following precipitation, which can contribute to pollution along with other sources. The "developed" land class, which encompasses open spaces, low, medium, and high-intensity areas, was determined for each TMDL stations' drainage area using ArcGIS and the 2021 NLCD (Dewitz 2023) dataset, and the results are shown in Table 2.

The NPDES stormwater industrial general permit (SCR000000) regulates industrial facilities that could potentially cause or contribute to violations of WQS through stormwater discharges. Similarly, the NPDES stormwater construction general permit (SCR100000) applies to construction activities. If construction activities have the potential to impact a water body with a TMDL, the SWPPP must address pollutants of concern and comply with the WLAs specified in this TMDL document. It's important to note that some stormwater discharges in the watershed may not fall under the SCS and SCR permits, and therefore they are not subject to the WLA portion of the TMDL.

Stormwater discharges from all regulated TS4 and MS4 entities operating within the TMDL watersheds have the potential to contribute to bacteria and other pathogens and are subject to the WLA portion of the TMDL. The SCDOT is a designated TS4 within these TMDL watersheds, operating under NPDES TS4 permit SCS040001 (Figure 5). However, SCDOT is not a traditional MS4 as it lacks statutory taxing or enforcement powers, and does not regulate land use or zoning, or issue building or development permits. Charleston County has been allocated a WLA (Table 7).

SSOs are intermittent point sources that can have a significant impact on water quality when they release into surface waters. The responsibility for preventing SSOs lies with the NPDES wastewater discharger or the operator of the collection system for non-permitted systems that handle wastewater. However, it is important to note that SSOs are not always preventable or reported. There is no sewer service in the TMDL watershed, therefore SSOs are not considered as a source in this TMDL watershed.




Figure 5. SCDOT TS4 and Charleston County MS4 are designated entities within the TMDL watershed.

The Department acknowledges that TS4 and MS4s may require multiple permit iterations to fully meet the assumptions and requirements of the TMDL. In order to comply with the TS4 and MS4 permit, making progress towards achieving the WLA reduction for the TMDL through compliance with the SWMP may be considered

sufficient, as long as the criteria of MEP are met. This allows for flexibility in the implementation process.

For SCDOT NPDES permitted TS4, existing and future NPDES MS4 permittees, compliance with the terms and conditions of their NPDES permit is an effective implementation of the WLA to the MEP and demonstrates consistency with the assumptions and requirements of the TMDL. For existing and future NPDES construction and industrial stormwater permittees, compliance with the terms and conditions of their permit is an effective implementation of the WLA. SCDES recognizes that adaptive management/implementation of these TMDLs might be needed to achieve the WQS.

3.2 Nonpoint Sources

Required load reductions in the LA portion of this TMDL can be implemented through voluntary measures and are eligible for the CWA §319 grants.

Nonpoint source pollution refers to pollution that originates from various sources across a large area, rather than being released through specific pipes. Nonpoint source pollution arises from a variety of land or water use activities, encompassing practices such as:

- Improper animal-keeping: Inadequate management of animal waste, runoff from livestock operations, and allowing livestock access to surface waters.
- Failing septic tanks: Malfunctioning or poorly maintained septic systems that release contaminants into groundwater or nearby water bodies.
- Agriculture: Runoff of fertilizers, pesticides, and sediment from agricultural lands.
- Forestry practices: Erosion and sedimentation resulting from logging activities and improper forest management.
- Wildlife: Animal waste and other natural sources contribute to water pollution.
- Urban and rural runoff: Surface runoff from developed areas (urban) and open spaces (rural), carrying pollutants like chemicals, oils, and litter into waterways.

These activities can lead to nonpoint source pollution, where pollutants are dispersed and do not have a single identifiable point of origin. These and other nonpoint source contributors located in unregulated areas can contribute to the presence of FC bacteria and other pathogens in these TMDL watersheds. Nonpoint sources in unregulated areas are addressed through the LA portion of the TMDL, rather than the WLA portion. During precipitation events, nonpoint source contributions of pathogens

to tidal streams are likely to increase as runoff carries pollutants from the land into waterways. Annual update for SFMA 12B points to nonpoint sources and storm water runoff to be the major source of FC exceedances (SCDHEC 2023).

3.2.1 Wildlife

Wildlife, including deer, feral pigs, squirrels, raccoons, opossums, waterfowl, and other birds, can contribute to the presence of bacteria and pathogens in waterways. Their feces may directly enter surface waters or be transported into streams through runoff after rainfall events. According to a study conducted in 2013, the SCDNR estimated deer density based on suitable habitats such as forests, croplands, and pastures. Based on this study, there is an estimated deer population of 30 to 45 per square mile in these TMDL watersheds (SCDNR 2013). Based on a study by Yagow (Yagow 2001), the bacteria production rate for deer was found to be 3.47×10^6 cfu/head-day, although only a portion of this bacteria will enter the water. As such, wildlife can be considered a potential source of FC and other pathogens in these watersheds.

3.2.2 Agriculture

Agricultural activities involving livestock or animal waste can contribute to pathogen contamination of surface waters. Animal feces can enter waterways through runoff or direct deposition. The large quantity of bacteria associated with animal waste makes agricultural activities a significant source of bacteria which can affect water quality. Effective management of manure and animal waste is essential to prevent pathogen contamination in the TMDL watersheds.

3.2.2.1 Agricultural Animal Facilities

Under SC R. 61-43, owners/operators of most commercial animal growing operations are required to obtain permits for the proper handling, storage, treatment, and disposal of manure, litter, and deceased animals (SCDHEC 2021). These regulations aim to safeguard water quality, ensuring that compliant facilities do not contribute to water quality impairments. South Carolina currently does not have CAFOs under NPDES coverage. Currently, there are no regulated agricultural operations within Russell Creek watershed.

3.2.2.2 Grazing Livestock

Livestock, particularly cattle, are recognized contributors of bacteria and other fecal-borne pathogens in waters. On average, cattle and horses typically produce approximately $1.0\text{E}+11$ cfu/day and $4.20\text{E}+08$ cfu/day per animal of FC bacteria, respectively (USEPA 2001). The presence of grazing cattle and other livestock can introduce bacteria into streams via runoff from pastures or through direct defecation into waters. The grazing of livestock in pastures is not regulated by SCDES.

The USDA National Agricultural Statistics Service's 2022 agricultural census reported 1,438 cattle and calves, and 503 horses and ponies in Charleston County (USDA 2024). Based on the assumption of an even distribution of cattle and horses across pasture/hay areas in Charleston County, approximate estimates of the cattle population within the TMDL watershed were calculated. It is estimated that cattle could contribute $1.08\text{E}+12$ cfu and horses could contribute $1.56\text{E}+09$ cfu per day to TMDL watersheds, with the possibility of some fraction entering the waterways (Table 4, Table 5).

The NLCD classification system, derived from the Anderson Land Cover Classification System, includes the "Pasture/Hay" category, which represents areas where grasses, legumes, or grass-legume mixtures are grown for livestock grazing or hay production on a perennial cycle. However, it should be noted that not all cattle included in the USDA census are grazed, as dairy cattle and feedlot cattle are often confined and not evenly distributed across Pasture/Hay areas. Therefore, the calculations provide an approximate estimation of the cattle population. Nonetheless, the direct discharge of fecal indicator bacteria and other pathogens into surface waters by cattle and other livestock remains a potential contributing source within the TMDL watersheds.

Table 4. Estimated bacteria contributions from cattle and calves in the TMDL watershed.

WQM Station	Pasture/Hay ac	n of Cattle and Calves in Station DA	Bacteria Produced in Station DA per day
12B-43	40.5	2.6	$2.59\text{E}+11$
12B-43A	128.1	8.2	$8.20\text{E}+11$

Table 5. Estimated bacteria contributions from horses and ponies in the TMDL watershed.

WQM Station	Pasture/Hay ac	n Horses and Ponies in Station DA	Bacteria Produced in Station DA per day
12B-43	40.5	0.9	3.74E+08
12B-43A	128.1	2.8	1.18E+09

3.2.3 Land Application of Industrial, Domestic Sludge or Treated Wastewater

Industrial and domestic wastewater treatment processes that are permitted under the NPDES program may produce solid waste byproducts, known as sludge. Some facilities are authorized to apply this sludge to designated land areas under specific conditions. Similarly, there are NPDES permitted facilities that can apply treated wastewater effluent to land at designated locations and under specific conditions. The regulations governing land application permits for these facilities can be found in SC R. 61-9 (SCDHEC 2023).

Proper management of the waste application is crucial to ensure that pollutants are effectively incorporated into the soil or taken up by plants, preventing their entry into streams or groundwater. If not managed correctly, land application sites can become a source of fecal pathogens and contribute to stream impairments. It's important to note that land application sites are not permitted to discharge directly into waterways. Any direct discharges from these sites to surface waters are illegal and can result in enforcement actions by SCDES.

It is recognized that there may be operating regulated land application sites located in this watershed. If properly managed, waste is applied at a rate that ensures pollutants will be incorporated into the soil or plants and pollutants will not enter streams. Land application sites can be a source of bacteria and other pathogens and contribute to stream impairment if not properly managed. The NPDES permitted land application sites are not allowed to directly discharge to surface waters. Direct discharges from land application sites to surface waters of the State are illegal and are subject to enforcement actions by SCDES. Currently, there are no NPDES permitted facilities with a land application permit for applying treated wastewater within these TMDL watersheds.

3.2.4 Leaking Sanitary Sewer and Illicit Discharges

Leaking sewer pipes and unauthorized sewer connections pose substantial risks to public health by releasing partially treated or untreated human waste into the environment. However, quantifying the full extent of these sources without direct monitoring is challenging, as their impact is contingent on variables like volume and proximity to surface water. Untreated domestic wastewater typically contains bacteria levels within the range of 10^4 to 10^6 MPN/100mL.

Illicit sewer connections reroute sewage into storm drains, causing direct sewage discharge through the storm drainage system's outfalls. To assess this issue, monitoring the storm drain outfalls during dry weather periods is crucial to determine the presence or absence of sewage within the drainage systems. This monitoring process is essential for identifying and documenting the extent of unauthorized sewer connections and their environmental impact.

Currently, there is no sewer service or sewer lines within Russel Creek TMDL watershed (SCDHEC 2023). Therefore, these are not considered as sources of bacteria impairments.

3.2.5 Failing Septic Systems

When installed and maintained properly, septic systems are safe, long-term options for treating wastewater and preserving valuable water resources. Regulations stipulate that permits for new septic tanks will not be issued when a wastewater treatment facility/public sewer line is accessible for connection.

SCDES has an enforcement program that investigates complaints regarding the functioning of an onsite wastewater system and if an unpermitted discharge of sewage or other domestic wastewater is identified, prompt timelines for compliance are issued to the responsible party in order to minimize the risk of any discharge presenting significant harm to the environment and public health. At present, the state lacks sufficient regulatory authority for maintenance and upkeep of onsite wastewater systems.

Based on the 2020 United States Census, there are approximately 69 housing units accommodating a population of 125 individuals within the TMDL watershed. According to the SFMA 12B annual update, sewer services are not present within the TMDL watershed, with waste management primarily reliant on septic systems.

Failing septic systems are identified as one of the potential sources contributing to bacteria exceedances in this TMDL watershed.

3.2.6 Stormwater Runoff

Domesticated pets, such as dogs and cats, are contributors of fecal indicator bacteria and other pathogens in urban and suburban areas. Wildlife species like deer, squirrels, raccoons, opossums, and birds also contribute to the overall bacteria load in these areas. Calculations based on the national pet statistics data from the AVMA suggest an estimated count of 101 dogs and 123 cats within the TMDL watersheds (AVMA 2022). These pets can contribute to the overall bacterial load in these specific areas.

Unregulated MS4 communities have the potential to contribute to fecal indicator bacteria and other pathogens through stormwater runoff. These unregulated entities are subject to the LA portion of the TMDL document.

3.2.7 Marinas, Boating Activities, and Structures

Currently, there are no marinas or pump out stations within the TMDL watershed, however, there are some private docks within the TMDL watershed area. Illegal discharges of untreated waste from boats can contribute to FC loadings in the TMDL watershed.

There are 3 main types of MSDs that are suitable for different kinds of marine vessels and have varying effluent treatment levels. Every vessel with an MSD installed as of January 30, 1980, must be equipped with one of the three types of MSDs (The United States Code 2012). Properly maintained MSDs should not be causing or contributing to bacteria exceedances in impaired waters. It is prohibited under Federal law to discharge untreated sewage from vessels within navigable waters as stated in the Clean Vessel Act.

Discharges of untreated sewage from boats and other watercraft can contribute to bacteria exceedances in the Russel Creek TMDL watershed.

4.0 Cumulative Probability Method

Cumulative probability distributions were used to calculate existing condition and percent reduction necessary to meet SFH WQS for FC in Russel Creek.

For the calculation of the cumulative probability distributions, data collected from station 12B-43A was used to calculate the percent reduction necessary to meet WQS. Data from this impaired station is summarized in Table 3. Data collected from 2020 through 2022 were used to calculate the percent reduction for shellfish monitoring station 12B-43A (Appendix A – Data Used for Calculation of the TMDL). Cumulative probability graph was created using Cumulative Probability Plot 3.0 (Boeing 2003) and log base 10 of bacteria data. If the data follow a log-normal distribution, the data points on the plot will approximate a straight line (the normal distribution). This straight line is then compared to the WQS at the appropriate percentile. For SFH in SC, the TMDL target equates to 43 mpn/100mL FC bacteria minus a 5% MOS (40.85 mpn/100mL, log10 1.61). Evaluating the data at the 90th percentile allows for the 10% exceedance as referenced in R. 61-68 (SCDHEC 2023), R. 61-47 (SCDHEC 2017), and NSSP (USFDA 2021). Figure 6 shows the cumulative probability plot for station 12B-43A.

This evaluation is consistent with the NSSP approach under the SRS scheme. According to the NSSP approach under an SRS scheme, if the data do not meet the SSM WQS, a line is drawn parallel to the original normal distribution line that intersects the standard at the 90th percentile. Drawing the line parallel to the original distribution assumes that the coefficient of variation remains the same for the original data and the desired water quality data (Novotny 2004). The necessary percent reduction is calculated as the difference between the distributions at the 90th percentile:

$$\frac{\text{Existing 90th \%tile concentration} - (WQS - MOS)}{\text{Existing 90th \%tile concentration}} \times 100$$

Targeting SSM percent reduction will be protective of the geometric mean standard. To demonstrate, SSM and geometric mean percent reductions based on data from 2020-2022 were calculated and compared to the overall SSM and geomean WQSs, which are 43 mpn/100 mL and 14 mpn/100 mL, respectively. As shown in Table 6, the estimated percent reduction for the geomean is less than the percent reduction for the SSM, so targeting the SSM should be protective of the geomean. Note that, SSM and geometric mean percent reductions shown on Table 6 are based on 43 mpn/100 and 14mpn/100 mL for SFH. Percent reduction shown on the Table 7 is based on SSM minus 5% MOS, and therefore is higher than those on Table 6.

Table 6. Single sample maximum and geometric mean percent reduction comparisons.

Station	n	SSM % Reduction	Geomean % Reduction	TMDL Data Period
12B-43A	36	51.7	9.43	2020-2022




Figure 6. Cumulative probability plot for station 12B-43A.

TMDLs for the impaired station listed in this document was calculated by estimating the cross-sectional area of the channel at the impaired station and estimating average tidal flow. TMDL load was based on the SSM WQS. Detailed description of the methodology along with an example calculation can be found in Appendix B - The Method Used for Calculate the Daily Load.

This method provides an estimate of the target daily load based on average tidal flow. Actual tidal flows and loads are highly variable at these locations. The estimated daily loading calculations are based on multiple assumptions such as dated NOAA station data, channel geometry, cross sectional area of the channel, flow velocities, channel depth, and the dynamic nature of the environment. Therefore, the resulting loadings are only provided as an example.

5.0 Development of the TMDL

5.1 Critical Conditions

Critical conditions are factors that either in combination or individually cause violations of WQS. In these TMDL watersheds, characterized by their tidal and complex hydrologic nature, determining a singular critical flow remains ambiguous. The implicit inclusion of critical conditions is achieved by considering data collected across all seasons over multiple years, diverse tidal states, and varying weather conditions during which the water samples were collected. This approach inherently addresses the range of potential critical conditions within the system.

5.2 Wasteload Allocation

The WLA is the portion of the TMDL allocated to NPDES permitted point sources. These point sources typically include industrial facilities, wastewater treatment plants, and other regulated dischargers.

It is important to note that the WLA does not cover illicit dischargers, including SSOs or other illegal sources. Illicit discharges are considered unauthorized and are not granted any allocation under the TMDL. These sources are illegal because they introduce pollutants into the water without proper permits or compliance with regulatory requirements.

The WLA is specifically designed to address the allowable pollutant loadings from permitted point sources, while other mechanisms and enforcement actions are typically employed to address and reduce the impacts of illicit discharges and SSOs to protect water quality and public health.

5.2.1 Continuous Point Sources

Russel Creek is classified as ORW, SFH, and recreational salt waters and dischargers to these waters are allowable if SCDES deems appropriate. Currently, there are no continuous NPDES permitted discharges to the affected TMDL watersheds with a bacteria effluent limit on their NPDES permit. Future continuous discharges are required to meet the prescribed loading for the pollutant of concern based on permitted flow and assuming an allowable permitted SSM of 43 mpn/100 mL. Continuous point source permit limits for bacteria are equivalent to the WQS.

5.2.2 Intermittent Point Sources

Intermittent point sources include all NPDES permitted stormwater discharges, including current and future TS4, MS4s, construction and industrial stormwater discharges covered under permits numbered SCS000000 & SCR100000 regulated under *SC Water Pollution Control Permits Regulation R. 61-9* (SCDHEC 2023). Illicit discharges, including SSOs, are not covered under any NPDES permit and are subject to enforcement mechanisms. Other non-urbanized areas may be required under the NPDES Phase II Stormwater Regulations to obtain a permit for the discharge of stormwater.

SCDOT TS4 and Charleston County MS4 are the regulated NPDES transportation and municipal MS4s located in the TMDL watersheds. SCDOT operates under NPDES TS4 Permit SCS040001 and owns and operates roads within the watershed. However, the Department recognizes that SCDOT is not a traditional MS4 in that it does not possess statutory taxing or enforcement powers. SCDOT does not regulate land use or zoning, or issue building or development permits.

Waste load allocations for stormwater discharges are expressed as a percent reduction instead of a numeric concentration due to the uncertain nature of stormwater discharge volumes and recurrence intervals. All current and future regulated stormwater discharges are required to meet the percentage reduction or the existing instream standard for the pollutant of concern. Table 7 presents the reduction needed for the impaired segment. The percent reduction identified for the impaired station in this document also applies to the bacteria waste loads attributable to those areas of the watershed which are covered or will be covered under TS4 and MS4 NPDES permits.

5.3 Load Allocation

The LA addresses nonpoint sources of FC, including unregulated processes and entities, and is expressed as a percentage reduction. Table 7 present the LA for the TMDL station as percentage reduction. If these nonpoint sources or any currently unregulated sources become regulated under NPDES TS4 or MS4 and are subject to SC R 61-68, they will be required to achieve the load reductions specified in the WLA component of the TMDL. This requirement also applies to future discharges from industrial and construction activities subject to SC R 61-9 (SCDHEC 2023).

5.4 Existing Load

Due to the tidal nature of the system, it is difficult to calculate an existing load for this system. For this reason, existing conditions are given as a concentration. The existing concentration is calculated as the concentration of FC bacteria at the 90th percentile based on the normal line fit to the monitoring data. The 90th percentile of the existing data is used to allow for the 10% exceedance outlined in the R. 61-68 and R. 61-47. The existing 90th percentile concentration for impaired station is shown in Table 7.

5.5 Margin of Safety

A MOS allows for an accounting of the uncertainty in the relationship between pollutant loads and receiving waters. MOS can be incorporated either explicitly or implicitly by using conservative assumptions. This TMDL has an explicit 5% MOS. Water quality data collected from shellfish monitoring station was compared to 40.85 mpn/100mL which is the SSM WQS minus 5% for FC for SFH.

5.6 Calculation of the TMDL

Bacteria data summarized in Table 3 and shown in Appendix A – Data Used for Calculation of the TMDL were used to calculate the TMDL for the impaired station. Station 12B-43, although not impaired, serves as the downstream station delineating the boundary for the area restricting shellfish harvest. Consequently, no reductions were computed for station 12B-43.

5.7 Reasonable Assurance

When a TMDL is developed for a pollutant that originates from both point and nonpoint sources, or from nonpoint sources only, USEPA guidance emphasizes the need to provide reasonable assurances that nonpoint source controls will effectively achieve their expected load reductions. For point sources, such as NPDES permitted dischargers, the WLA provided in their permits already ensures this assurance.

However, for unregulated nonpoint sources of pollutants, achieving the necessary load reductions can be more challenging. To address this, various measures can be employed, including the implementation of BMPs, local ordinances, and outreach and educational efforts. CWA §319 grant funding may be available to interested parties for the purposes of implementing these measures.

Based on the information available at this time, the portions of the watersheds that drain directly to a regulated TS4 and MS4 and that which drain through the non-regulated TS4 and MS4 have not been clearly defined. Loading from both types of sources (regulated and non-regulated) typically occurs in response to rainfall events, discharge volumes and recurrence intervals are largely unknown. Therefore, where applicable, the regulated TS4 and MS4 are assigned the same percent reductions as the non-regulated sources in the watershed. Compliance with the TS4 and MS4 permit regarding this TMDL document is determined at the point of discharge to the waters of the state. The regulated MS4 entity is only responsible for implementing the TMDL WLA by following their MS4 permit requirements and is not responsible for reducing loads prescribed as LA in this TMDL document.

Table 7. TMDL for Russell Creek. TMDL is expressed as the mpn/100 mL and mpn/day, and allocations are expressed as % reductions.

Station	Existing Conc. (mpn/100mL)	TMDL Conc. ¹ (mpn/100mL)	TMDL Load ² (WLA+LA+MOS) (mpn/day)	Implementation Targets ⁶			
				Continuous Sources ³ (mpn/100mL)	Intermittent MS4 ⁵ (%)	Intermittent TS4 SCDOT (%) ⁴	Nonpoint Sources (%)
12B-43A	88.3	43	1.68E+12	See Note Below	53.7%	53.7% ⁴	53.7%

Table Notes:

1. TMDL = SFH WQS for single sample maximum not to exceed 43 mpn/100 mL fecal coliform.
2. TMDL at average flow conditions calculated using estimated average tidal flow at the WQ station. See Appendix B for example calculation.
3. WLA is expressed as a daily maximum of 43 mpn/100 mL FC. There are no continuous dischargers at this time. Future continuous discharges are required to meet the WQS for the pollutant of concern. Loadings to meet the WQS are developed based on the permitted flow and an allowable permitted maximum concentration of 43 mpn/100mL FC.
4. By implementing the BMPs that are prescribed in either the SCDOT annual SWMP or the SCDOT NPDES TS4 permit to address bacteria, the SCDOT will comply with this TMDL and its applicable WLA to the MEP as required by its NPDES TS4 permit.
5. Percent reduction applies to all NPDES permitted stormwater discharges, including current and future MS4s, construction, and industrial discharges covered under permits numbered SCS & SCR. Stormwater discharges are expressed as a percentage reduction due to the uncertain nature of stormwater discharge volumes and recurrence intervals. Stormwater discharges are required to meet percentage reduction or the existing instream standard for the pollutant of concern in accordance with their NPDES Permit.
6. Refer to section 6.0 for the derivation of implementation targets.

6.0 Implementation

As implementation strategies progress, SCDES will continue to monitor the effectiveness of these measures and evaluate water quality where deemed appropriate. SCDES recognizes that adaptive management might be necessary to achieve the WQS and we are committed to targeting the load reductions needed to improve water quality in these TMDL watersheds. As additional data and/or information become available, it may become necessary to revise and/or modify the TMDL target accordingly. The implementation strategies presented below are not inclusive and are only provided as guidance.

6.1 Continuous Sources

NPDES permitted continuous point sources are required to meet the instream WQS for bacteria at the discharge point (end of pipe). Currently, there are no point source discharges to TMDL watersheds described in this document.

6.1 Intermittent Point Sources – MS4s

NPDES permitted TS4 and MS4 entities are required to target and show progress towards implementing the calculated percent reductions to the MEP with each permit cycle by following their permit requirements. These entities are responsible for documenting and reporting their progress toward achieving the percent reductions allocated to the MS4s in these TMDL watersheds.

An iterative approach of water quality monitoring, illicit source detection and elimination, deploying BMPs and evaluation of their effectiveness, outreach and education, optimization of other tools such as local ordinances, and revision of their stormwater management plan (SWMP) as needed in reducing bacteria loading to these TMDL watersheds is expected to show improvements in water quality.

For SCDOT TS4, Charleston County MS4, and future NPDES MS4 permittees, compliance with terms and conditions of its NPDES permit is effective implementation of the WLA to the MEP. For existing and future NPDES construction and industrial stormwater permittees, compliance with the terms and conditions of its permit is an effective implementation of the WLA.

6.2 Nonpoint Sources

South Carolina has several tools available for implementing the nonpoint source component of this TMDL. The Nonpoint Source Management Plan document is one example (SCDHEC 2019).

Required load reductions in the LA portion of this TMDL can be implemented through voluntary measures and are eligible for CWA §319 grants. Interested parties, such as local stakeholder groups, universities, local governments, etc., may be eligible to apply for CWA §319 grants to install BMPs that will implement the LA portion of these TMDLs and reduce nonpoint source bacteria and other pathogen loadings to impaired waters. Congress amended the CWA in 1987 to establish the §319 Nonpoint Source Management Program. Under §319, States receive grant money to support a wide variety of activities including the restoration of impaired waters. TMDL implementation projects are given the highest priority for §319 funding. CWA §319 grants are not available for implementation of the WLA component of these TMDLs but may be available for the LA component within permitted TS4 and MS4 jurisdictional boundaries.

7.0 References

2017. "40 CFR - Protection of Environment." *Subchapter D Water Programs Part 130 Water Quality Planning and Management*. July 1.
- AVMA. 2022. "U.S. Pet Statistics." <https://www.avma.org/resources-tools/reports-statistics/us-pet-ownership-statistics#formulas>.
- Boeing. 2003. "Cumulative Probability Plot 3.0."
- Dewitz, J. 2023. "National Land Cover Database (NLCD) 2021 Products." <https://www.usgs.gov/data/national-land-cover-database-nlcd-2021-products>.
- Griffith, G. E., J. M. Omernik, J. A. Comstock, M. P. Schafale, W. H. McNab, D. R. Lenat, T. F. MacPherson, J. B. Glover, and V. B. Shelburne. 2002. "Ecoregions of North Carolina and South Carolina, (color poster with map, descriptive text, summary tables, and photographs)." Reston, Virginia: U.S. Geological Survey (map scale 1:1,500,00).
- Novotny, Vladimir. 2004. "Simplified Data Based Total Maximum Daily Loads, or the World is Log-Normal." *Journal of Environmental Engineering* 130 (6): 674-683.
- SCDHEC. 2012. "Classified Waters (R. 61-69)." Columbia, SC: Bureau of Water, June.
- SCDHEC. 2019. *Nonpoint Source Management Plan 2020-2024*. SCDHEC Bureau of Water. <https://scdhec.gov/environment/your-water-coast/watersheds-program/section-319-nonpoint-source-program>.

- SCDHEC. 2021. *R. 61-43 Standards for the Permitting of Agricultural Animal Facilities*. Effective June 28, 2002. Columbia, SC. Accessed March 19, 2018.
<http://www.scdhec.gov/Agency/docs/water-regs/r61-43.pdf>.
- . 2023. "R. 61-68 Water Classifications and Standards."
- SCDHEC. 2017. "Regulation 61-47 Shellfish."
- SCDHEC. 2023. "Shellfish Management Area 12B 2023 Annual Update."
- SCDHEC. 2023. "The State of South Carolina's 2020 and 2022 Integrated Report (IR) Part I: Section 303(d) Listing of Impaired Waters."
- SCDHEC. 2023. *Water Pollution Control Permits: R61-9*. May.
<https://scdhec.gov/BOW/water-regulations-standards/water-regulations-standards-water-pollution-control>.
- SCDNR. 2013. *South Carolina Deer Density Map*.
<https://www.dnr.sc.gov/wildlife/deer/deermap.html>.
- The United States Code. 2012. "33 U.S.C. 1322 - Marine Sanitation Devices." *United States Code, 2006 Edition, Supplement 5, Title 33 -Navigation and Navigable Waters*. January 3.
- USDA. 2024. *2022 Census of Agriculture*. National Agricultural Statistics Service, United States Department of Agriculture, 604.
https://www.nass.usda.gov/Publications/AgCensus/2022/Full_Report/Volume_1,_Chapter_2_County_Level/South_Carolina/.
- USEPA. 2001. *Protocol for developing pathogen TMDLs*. Washington DC: Office of Water (4503F), 132.
- USFDA. 2021. "National Shellfish Sanitation Program (NSSP). Guide for the Control of Molluscan Shellfish." <https://www.fda.gov/media/143238/download>.
- Yagow, G. 2001. *Fecal Coliform TMDL, Mountain Run watershed Culpeper County, Virginia*. Virginia Tech, Virginia Department of Environmental Quality, Virginia Department of Conservation and Recreation.

Appendix A – Data Used for Calculation of the TMDL

Date 12B-43A	mpn/ 100 mL	Date 12B-43A	mpn/ 100 mL
1/15/2020	13	1/19/2022	7
2/12/2020	33	2/14/2022	2
3/30/2020	8	3/2/2022	11
4/22/2020	110	4/13/2022	13
5/19/2020	64	5/23/2022	8
6/15/2020	79	6/15/2022	5
7/20/2020	17	7/20/2022	350
8/12/2020	2	8/22/2022	13
9/2/2020	23	9/12/2022	13
10/19/2020	17	10/25/2022	23
11/16/2020	33	11/13/2022	33
12/21/2020	33	12/14/2022	13
1/13/2021	17		
2/10/2021	33		
3/2/2021	49		
4/19/2021	17		
5/19/2021	23		
6/21/2021	350		
7/19/2021	21		
8/11/2021	5		
9/13/2021	17		
10/12/2021	49		
11/15/2021	23		
12/14/2021	22		

Appendix B - The Method Used for Calculate the Daily Load

Calculating a target load begins with the determination of average tidal flow. First, the average cross-sectional area of the waterway at the sampling station is estimated using the mean tidal range, average depth at low tide, the average width of the channel, and channel geometry (rectangular vs triangular). Lacking site-specific data, average depth at low tide and average widths may be obtained from navigation charts, satellite imagery, topo maps, etc. Mean tidal range is determined as the difference between mean high and mean low water levels and is retrieved from NOAA's Tides and Currents web page using the NOAA station most appropriate for the sampling location. Though infrequently, mean tidal range may also be readily available for some stations. Where available, tidal velocity is determined from the time of travel or flow study data. Usually, these data are not available and default ranges are used (Table 8).

Table 8. Default velocities to be used in the absence of site-specific data.

Velocity (ft/sec)	Waterbody Characteristic
0.5 – 1.0	Relatively slow, constricted estuaries
1.0 – 2.0	Moderate, free-flowing estuaries
2.0 – 3.0	Rapid, highly tidal estuaries

Average tidal flow is calculated by multiplying velocity by the cross-sectional area of the waterbody at the sampling station.

The TMDL loads are then calculated by subtracting the 5% MOS from the WQS and multiplying the resulting concentration by average tidal flow and a conversion factor (24,465,758.4 sec*mL / ft³*day) as demonstrated below.

This method provides an estimate of the target daily load based on average tidal flow. Actual tidal flows and loads are highly variable at this location. Therefore, the TMDL expression includes concentration and percent reduction targets for implementation.

Calculations for 12B-43A:

Average depth at low tide: 2 ft

Average width: 320.2 ft

Mean tidal range: 5.99 ft

Channel shape: triangular

Channel area = $2\{(320.2/2) * (0.5 (2 + 5.99/2))\} = 799.7 \text{ ft}^2$

Average tidal flow = $799.7 \text{ ft}^2 * 2 \text{ ft/s} = 1599.4 \text{ cfs}$

WLA + LA = 40.85 mpn/100 mL

WLA + LA load = 40.85 mpn/100 mL * 1599.4 ft³/sec * 24,465,758.4 sec*mL/ft³*day =
1.6E+12 mpn/day

MOS Load = 2.15 mpn/100 mL * 1599.4 ft³/sec * 24,465,758.4 sec*mL/ft³*day =
8.41E+10

TMDL = 1.68E+12

Responsiveness Summary

One comment was received from SCDOT.

SCDOT:

Comment 1: Comments on the Initial Draft of the Russell Creek TMDL

The South Carolina Department of Transportation (SCDOT) concurs with the language presented in the draft public notice for the Russell Creek TMDL, posted on May 14, 2025, at 12:00 AM.

If the South Carolina Department of Environmental Services (SCDES) receives any public comments that would substantially alter the intent of the TMDL, SCDOT requests either an extension of the public comment period or re-advertisement of the notice to allow adequate time to review and respond to the proposed changes.

Response 1:

DES received no other comments on this TMDL, and no changes were made. DES follows the administrative procedures required by S.C. Regulation 61-110. Per the regulation, a Notice of Proposed Decision, including comments, responses and changes appearing in the final draft TMDL, is made available to those persons providing comment in response to the public notice and to those persons participating at an informational hearing. The Notice of Proposed Decision may be appealed as a contested case in accordance with the S.C. Administrative Procedures Act.