

Total Maximum Daily Load Document

E-035, E-092, E-007B, E-008, E-099
North Fork Edisto River

Hydrologic Unit Codes 030502030308, 030502030306, 030502030305, 030502030304, 030502030301,
030502030303, 030502030302, 030502030209, 030502030210, 030502030208, 030502030207, 030502030203,
030502030204, 030502030202, 030502030201, 030502030105, 030502030106, 030502030103, 030502030102,
030502030101, 030502030104, 030502030205, 030502030206

Fecal Coliform Bacteria,
Indicator for Pathogens



March 2011
Prepared for:
Bureau of Water



Prepared by:
Ann-Marie Altman
SCHDEC Technical Document Number 4A21-11

Abstract

§303(d) of the Clean Water Act (CWA) and EPA's Water Quality Planning and Management Regulations (40 CFR Part 130) require states to develop total maximum daily loads (TMDLs) for water bodies that are not meeting designated uses under technology-based pollution controls. A TMDL is maximum amount of pollutant a waterbody can assimilate while meeting water quality standards for the pollutant of concern. All TMDLs include a wasteload allocation (WLA) for all National Pollutant Discharge Elimination System (NPDES)-permitted discharges, a load allocation (LA) for all nonpoint sources, and an explicit and/or implicit margin of safety margin of safety (MOS). A fecal coliform TMDL was developed for stations # E-035, #E-092, #E-099, #E-007B, and # E-008 within the North Fork Edisto River watershed located in Lexington, Aiken, Calhoun, and Orangeburg Counties, SC. The impaired stations are included on the State's 2010 §303(d) list due to excessive fecal coliform numbers documented during the 2004 - 2008 assessment period. Between 1999-2008, 8 percent of the samples collected at impaired monitoring station E-092 exceeded the water quality standards, while 15 percent of the samples at E-007B, 11 percent of the samples at E-008, 14 percent at E-099 and 9 percent of the samples at E-035 exceeded the water quality standards.

This watershed is predominantly forest and agricultural lands. Probable causes of fecal contamination include agricultural runoff, failing septic systems, leaking sewers, sanitary sewer overflows, and urban runoff. The load-duration curve methodology was used to calculate existing and TMDL loads for each impaired segment. Existing pollutant loadings and proposed TMDL reductions for critical hydrologic conditions are presented in Table Ab-1. Critical hydrologic conditions were defined as either moist, mid-range, or dry depending on which condition demonstrated the highest load reductions necessary to meet water quality standards. In order to achieve the target load (slightly below water quality standards) for this portion of the North Fork Edisto River watershed, reductions in the existing loads of up to 71% will be necessary at station #E-035, 5% at station #E-092, 30% at station #E-007B, 5% at station #E-099 and 19% at station #E-008. For SCDOT, existing and future NPDES MS4 permittees, compliance with terms and conditions of its NPDES permit is effective implementation of the WLA to the Maximum Extent Practicable. For existing and future NPDES construction and Industrial stormwater permittees, compliance with terms and conditions of its permit is effective implementation of the WLA. Required load reductions in the LA portion of this TMDL can be implemented through voluntary measures and are eligible for CWA §319 grants.

The Department recognizes that **adaptive management/implementation** of this TMDL (i.e. WLA and LA) might be needed to achieve the water quality standard and we are committed towards targeting the load reductions to improve water quality in the North Fork Edisto watershed. As additional data and/or information becomes available, it may become necessary to revise and/or modify the TMDL target accordingly.

Table Ab-1. Total Maximum Daily Loads for the North Fork Edisto River Watershed. Loads are expressed as colony forming units (cfu) per day.

Station	Existing Load (cfu/day)	TMDL (cfu/day)	Margin of Safety (MOS) (cfu/ day)	Wasteload Allocation (WLA)		Load Allocation (LA)	
				Continuous Sources ¹ (cfu/day)	Non-continuous Sources ^{2,3,4} (% Reduction)	Load Allocation (cfu/day)	% Reduction to Meet LA ³
E-035	7.62E+12	2.79E+12	1.39E+11	NA	71%	2.65E+12	71%
E-092	3.15E+12	3.86E+12	1.93E+11	NA	5%	3.67E+12	5%
E-007B	2.77E+11	2.04E+11	1.02E+12	NA	30%	1.94E+11	30%
E-008	6.25E+12	5.34E+12	2.67E+11	2.57E+8	19%	5.07E+12	19%
E-099	7.11E+12	7.11E+12	3.56E+11	NA	5%	6.76E+12	5%

Table Notes:

1. WLAs are expressed as a daily maximum; NA = not applicable, no point sources. Continuous discharges are required to meet the prescribed loading or the existing instream standard for the pollutant of concern. Loadings were developed based upon permitted flow and an allowable permitted maximum concentration of 400cfu/100ml.
2. Percent reduction applies to all NPDES-permitted stormwater discharges, including current and future MS4, construction and industrial discharges covered under permits numbered SCS & SCR. Stormwater discharges are expressed as a percentage reduction due to the uncertain nature of stormwater discharge volumes and recurrence intervals. Stormwater discharges are required to meet percentage reduction or the existing instream standard for pollutant of concern in accordance with their NPDES permit.
3. Percent reduction applies to existing instream load.
4. By implementing the best management practices that are prescribed in either the SCDOT annual SWMP or the SCDOT MS4 permit to address fecal coliform, the SCDOT will comply with this TMDL and its applicable WLA to the maximum extent practicable (MEP) as required by its MS4 permit

CONTENTS

1.0 Introduction	7
1.1 Background	7
1.2 Watershed Description.....	8
1.3 Water Quality Standard.....	16
2.0 WATER QUALITY ASSESSMENT	16
3.0 SOURCE ASSESSMENT AND LOAD ALLOCATION	18
3.1.1 Continuous Point Sources	18
3.2.3 Leaking Sanitary Sewers and Illicit Discharges	26
3.2.4 Failing Septic Systems	26
4.0 LOAD-DURATION CURVE METHOD	27
5.0 DEVELOPMENT OF TOTAL MAXIMUM DAILY LOAD	29
5.1 Critical Conditions	29
5.2 Existing Load	29
5.3 Wasteload Allocation	30
5.3.1 Continuous Point Source.....	30
5.4 Load Allocation	32
5.5 Seasonal Variability	32
5.6 Margin of Safety.....	32
6.0 Implementation	35
7.0 RESOURCES FOR POLLUTION MANAGEMENT	42
7.1 General for Urban and Suburban Stormwater Mitigation.....	43
7.2 Illicit Discharges.....	44
7.3 Pet Waste	44
7.4 Wildlife.....	45
7.5 Septic Systems.....	45
7.6 Field Application of Manure.....	45
7.7 Grazing Management	45
7.8 Animal Feeding Operations and Barnyards	46
7.9 Federal Agriculture Resources: Program Overviews, Technical Assistance, and Funding.....	46

8.0 REFERENCES AND BIBLIOGRAPHY 49

LIST OF APPENDICES

Appendix A Additional Rain Charts by station.....51

Appendix B Additional Load Duration Curve Graphs by Station..... 53

Appendix C Data Tables.....55

Appendix D Fecal Coliform Water Quality Data Summary for Impaired Stations By Date.....60

Appendix E Watershed Photos..... 67

Appendix F Evaluating the Progress of MS4 Programs: Meeting the Goals of TMDLs and Attaining Water Quality Standards70

LIST OF TABLES

Table Ab-1. Total Maximum Daily Loads for the North Fork Edisto Watershed.....iii

Table 1. North Fork Edisto River Watershed List of Impaired Stations.....7

Table 2a. North Fork Edisto Watershed Total Land Use.....11

Table 2b. Developed Land Use from Reach to Reach.....13

Table 3. Fecal Coliform WQS Exceedence Summary for Impaired Stations E-035, E-092, E-007B, E-008 (2001-2006).....17

Table 4. NPDES Treated Sanitary Waste Dischargers in the North Fork Edisto Watershed.....19

Table 5. Permitted Active Animal Feeding Operations within the North Fork Edisto River Watershed.....22

Table 6. Percent Reduction Necessary to Achieve Target Load by Hydrologic Category.....30

Table 7. Average Monthly Permitted Flow and WLAs for the NPDES Wastewater Discharges in the North Fork Edisto Watershed.....30

Table 8. Percent Reduction Necessary to Achieve Target Load.....31

Table 9. TMDL Components for the Fecal Coliform Impaired Segments in the North Fork Edisto River and Tributary Watershed..... 33

LIST OF FIGURES

Figure 1a. SCDHEC Monitoring Stations Impaired with Excessive Fecal Coliform Numbers.....9

Fibure 1b. Station Reaches.....10

Figure 2a. Land Use of Entire Watershed.....12

Figure 2b. Land Use Reach to Reach.....13

Figure 3. Precipitation Graph and Fecal Coliform Data by Date.....17

Figure 4. SCDOT Roads and Buildings.....20

Figure 5. Load Duration Curve for North Fork Edisto Station E-035.....28

1.0 Introduction

1.1 Background

Fecal coliform bacteria are widely used as an indicator of pathogens in surface waters and wastewater. The presence of FCs in surface waters may signify a presence of pathogens, which in turn leads to a greater risk of health for individuals participating in recreational activities within the water body (USEPA, 2001). Acute gastrointestinal illnesses affect millions of people in the United States and cause billions of dollars of costs each year (Gaffield et al. 2003). Of these illnesses many are caused by contaminated drinking water. Untreated stormwater runoff has been associated with a number of disease outbreaks, most notably an outbreak in Milwaukee that caused many deaths in 1993.

Though occurring at low levels from natural sources, the concentration of fecal coliform bacteria can be elevated in water bodies as the result of pollution. Sources of fecal coliform bacteria are usually diffuse or nonpoint in nature and originate from stormwater runoff, failing septic systems, agricultural runoff, leaking sewers among other sources. Occasionally, the source of the pollutant is a point source. Section 303(d) of the Clean Water Act (CWA) and EPA's Water Quality Planning and Management Regulations (40 CFR Part 130) require states to develop TMDLs for water bodies that are not meeting designated uses under technology-based pollution controls. The TMDL process establishes the allowable loading of pollutants or other quantifiable parameters for a water body based on the relationship between pollution sources and in stream water quality conditions so that states can establish water quality-based controls to reduce pollution and restore and maintain the quality of water resources (USEPA 1991).

The State of South Carolina has placed five monitoring stations in the North Fork Edisto River watershed on South Carolina's 2010 §303(d) list for impairment due to fecal coliform bacteria. These stations are identified in Table 1 and Figure 1.

Table 1. North Fork Edisto River Watershed Fecal Coliform Impaired Waters.

Waterbody	Station Number	Description
North Fork Edisto River	E-092	North Fork Edisto River at SC 3 5.5 miles Northwest of North
North Fork Edisto River	E-007B	North Fork Edisto River 4 miles below E-007 at a cabin
North Fork Edisto River	E-008	North Fork Edisto River at S-38-39 WSW of Rowesville
Bull Swamp Creek	E-035	Bull Swamp Creek at US 321 0.9 miles South of Swansea
North Fork Edisto River	E-099	North Fork Edisto River at S-38-74 NW of Orangeburg

It should be noted that impaired monitoring station E-105 (Caw Caw Swamp) is also located within this watershed, however it has been addressed in a separate TMDL document (see technical

document 4A-10). A portion of the upper watershed has already been addressed in a separate TMDL as well (see technical document 012-07). Both of these areas are included in the total delineated drainage area for impaired stations addressed in this TMDL, however they are not included in assessments for each impaired station's reach.

1.2 Watershed Description

The headwaters of the North Fork Edisto River are located near the town of Batesburg in Lexington County. It flows in a southeasterly direction eventually flowing into the Edisto River near the city of Branchville in Orangeburg County. The North Fork Edisto River watershed (HUCs 030502030101, 030502030102, 030502030104, 030502030103, 030502030106, 030502030105, 030502030201, 030502030204, 030502030202, 030502030206, 030502030208, 030502030210, 030502030205, 030502030207, 030502030303, 030502030302, 030502030301, 030502030305, 030502030306, 030502030308, 030502030203, 030502030209, 030502030304) drains approximately 728.16 square miles. However, for the purposes of this TMDL the total drainage area used in the land use summary (reach to reach, excluding the two previous TMDLs' drainage areas) is 533 square miles. It is located within the Edisto River basin (see Figure 1). There are 5 impaired sites within this watershed and each will be addressed as it's own reach in the document. Reach 1 addresses the area from E-092 and E-035 to the top of the watershed; Reach 2 addresses station E-035; Reach 3 is the area from E-099 to E-035 and E-092; Reach 4 is the area from E-007B to E-099; Reach 5 is the area from E-008 to E-007B.

**Figure 1a. Location of Impaired SCDHEC Monitoring Stations-
North Fork Edisto TMDL Total Drainage Area**





Figure1b. Location of Station Reaches



Land use within the watershed is predominately forest (40.04%) and agricultural lands (22.48%) (NLCD 2001). Developed lands (residential, commercial, industrial or open urban space) comprise approximately 7.6% of the watershed (Table 2; Figure 2).

Table 2a. North Fork Edisto Watershed Land Use (derived from NLCD 2001).

Land Use (NLCD 2001)	Area (mi²)	Percent
Woody Wetlands	79.74	10.95%
Open Water	5.5	0.76%
Emergent Herbaceous Wetlands	1.74	0.24%
Total Wetlands/Open Water	86.98	11.95%
Evergreen Forest	180.55	24.8%
Deciduous Forest	87.67	12.04%
Mixed Forest	23.31	3.2%
Total Forested	291.53	40.04%
Cultivated Crops	96.34	13.23%
Pasture/Hay	67.39	9.25%
Total Agricultural	163.73	22.48%
Developed, Open Space	39.57	5.43%
Developed, Low Intensity	11.69	1.6%
Developed, Medium Intensity	3.0	0.41%
Developed, High Intensity	1.19	0.16%
Total Developed	55.45	7.6%
Scrub/Shrub	5.02	0.69%
Grassland/Herbaceous	125.46	17.23%
Total Other	130.48	17.92%
Total Area	728.2	100%

**Figure 2a. Land Use Within the North Fork Edisto TMDL
Total Delineated Watershed Drainage Area**

**North Fork Edisto TMDL
Impaired Stations E-008, E-007B, E-099, E-035, E-092
Drainage Area = 728.16 sq. miles**




Table 2b. Developed Area From Reach to Reach

<i>Station Reach</i>	<i>Total Drainage Area of Station Reach (sq. miles)</i>	<i>Total Developed Area (sq. miles)</i>	<i>Percent Developed Area (%)</i>
1. From E-092 and E-035 to top of Watershed	188.48	10.54	5.59
2. E-035	75.14	5.69	7.58
3. From E-099 to E-035 and E-092	203.8	11.19	5.48
4. From E-007B to E-099	36.86	8.97	24.34
5. From E-008 to E-007B	28.83	2.13	7.42
Total	533.11	36.3	6.81

Figure 2b. Land Use for Reach 1




Figure 2c. Land Use for Reach 2




Figure 2d. Land Use for Reach 3




Figure 2e. Land Use for Reach 4





Figure 2f. Land Use for Reach 5



1.3 Water Quality Standard

The impaired stream segment of the North Fork Edisto River basin is designated as Class Freshwater. Waters of this class are described as:

“Freshwaters (FW) are freshwaters suitable for primary and secondary contact recreation and as a source for drinking water supply after conventional treatment in accordance with the requirements of the Department. Suitable for fishing and the survival and propagation of a balanced indigenous aquatic community of fauna and flora. Suitable also for industrial and agricultural uses.” (R.61-68)

South Carolina’s Water Quality Standard (WQS) for fecal coliform in freshwater is:

“Not to exceed a geometric mean of 200/100 mL, based on five consecutive samples during any 30 day period; nor shall more than 10% of the total samples during any 30 day period exceed 400/100 mL.” (R.61-68).

Primary contact recreation is not limited to large streams and lakes. Even streams that are too small to swim in will allow small children the opportunity to play and immerse their hands and faces. The current water quality standard protects all surface water for primary use recreation.

2.0 WATER QUALITY ASSESSMENT

The South Carolina Department of Health and Environmental Control (SCDHEC) conducts monitoring at five locations within the North Fork Edisto watershed (SCDHEC 2004). Monitoring is conducted at stations E-007, E-007B, E-008, E-099 and E-035.


Waters in which no more than 10% of the samples collected over a five year period are greater than 400 fecal coliform counts or cfu/100 ml are considered to comply with the South Carolina WQS for fecal coliform bacteria. Waters with more than 10% of samples greater than 400 cfu/100 ml are considered impaired for fecal coliform bacteria and placed on South Carolina’s §303(d) list¹. The North Fork Edisto (E-092, E-007B, E-008, E-035, E-099) is considered impaired due to fecal coliform WQS exceedences. Table 3 provides a summary of number of samples collected, number of exceedences and exceedence percentage. A detailed list of all samples by date with their respective water quality data is presented in Appendix C at the end of this document. Figure 3 illustrates precipitation and fecal coliform by date for E-035. Additional rain charts by station are presented in Appendix A. For E-092 a positive correlation was observed between FC and rain ($r = 0.10$). E-035, E-099 and E-008 also have a positive correlation between FC and rain (E-035, $r = 0.38$; E-099, $r = 0.2$; E-008, $r = 0.14$). E-007B has a weak positive correlation ($r = 0.02$).

¹ The frequency of sampling was fewer than five samples within a 30 day period, therefore the water quality assessment was based on the 10% standard (400/100 mL).

Table 3. Fecal Coliform WQS Exceedence Summary for Impaired Stations E-092, E-007B, E-008, E-035, E-099 (1999-2006; time-frame not consistent with that of 2010 303(d) listing cycle).

Station	Waterbody	Number of Samples	Number Samples >400/100mL	% Samples Exceed WQS
E-092	North Fork Edisto River	47	4	8 %
E-007B	North Fork Edisto River	47	7	15 %
E-008	North Fork Edisto River	47	5	11 %
E-035	Bull Swamp Creek	36	3	9 %
E-099	North Fork Edisto River	93	13	14%

Figure 3. Precipitation and Fecal Coliform Data by Date for E-035



3.0 SOURCE ASSESSMENT AND LOAD ALLOCATION

Fecal coliform bacteria are used by the State of South Carolina as the indicator for pathogens in surface waters. Pathogens, which are usually difficult to detect, cause disease and make full body contact recreation in lakes and streams a risk to public health. Indicators such as fecal coliform bacteria, enterococci, or *E. coli* are easier to measure, have similar sources as pathogens, and persist in surface waters for a similar or longer length of time. These bacteria are not in themselves disease causing, but indicate the potential presence of organisms that may result in sickness.

There are many sources of pathogen pollution in surface waters. In general these sources may be classified as point and nonpoint sources. With the implementation of technology-based controls, pollution from continuous point sources, such as factories and wastewater treatment facilities, has been greatly reduced. These point sources are required by the (CWA) to obtain a NPDES permit. In South Carolina NPDES permits require that dischargers of sanitary wastewater must meet the state standard for fecal coliform at the point of discharge. Municipal and private sanitary wastewater treatment facilities may occasionally be sources of pathogen or fecal coliform bacteria pollution. However, if these facilities are discharging wastewater that meets their permit limits, they are not causing impairment. If any of these facilities is not meeting its permit limits, enforcement actions/mechanisms are required.

Other non-continuous point sources required to obtain NPDES permits that may be a source of pathogens include Municipal Separate Storm Sewer Systems (MS4s) and stormwater discharges from construction or industrial sites. MS4s may require NPDES discharge permits under the NPDES Stormwater regulations. These sources are also required to comply with the state standard for the pollutant(s) of concern. If discharges from regulated MS4 entities and from construction and industrial sites meet the percentage reduction or the water quality standard as prescribed in Section 5 of this TMDL document and required in their permit(s), they should not be causing or contributing to an instream FC bacteria impairment.

3.1 Point Sources

Point sources are defined as pollutant loads discharged at a specific location from pipes, outfalls, and conveyance channels from either municipal wastewater treatment plants, industrial waste treatment facilities, or regulated stormwater discharges. Point sources can also include pollutant loads contributed by tributaries to the main receiving water stream or river. Point sources can be further broken down into continuous and non-continuous.

3.1.1 Continuous Point Sources

Currently there are twenty-one NPDES discharges in the North Fork Edisto watershed, however only the domestic sanitary dischargers are permitted to discharge fecal coliform. There is currently one permitted domestic sanitary discharger in the North Fork Edisto watershed. This will be the only NPDES discharger assigned a WLA for FC. Future NPDES discharges in the referenced watershed are required to implement the WLA and demonstrate consistency with the assumptions and requirements of the TMDL. Table 4 shows the NPDES treated sanitary waste discharger along with the closest downstream impaired segment that receives the discharge.

Table 4. NPDES Treated Sanitary Waste Dischargers in the North Fork Edisto Watershed.

Impaired Station	Facility Name	Permit #	Type
E-008	Edisto High School	SC0040185	Minor domestic

3.1.2 Non-Continuous Point Sources

Non-continuous point sources include all NPDES-permitted stormwater discharges, including current and future MS4s, construction and industrial discharges covered under permits numbered SCS and SCR and regulated under SC Water Pollution Control Permits Regulation 122.26(b)(14)&(15). All regulated MS4 entities have the potential to contribute FC pollutant loadings in the delineated drainage area used in the development of this TMDL.

The South Carolina Department of Transportation (SCDOT) is currently the only designated Municipal Separate Storm Sewer System (MS4) within the watershed. The SCDOT operates under NPDES MS4 SCS040001 and owns and operates roads in the watershed (Figure 4). However, the Department recognizes that SCDOT is not a traditional MS4 in that it does not possess statutory taxing or has enforcement powers. SCDOT does not regulate land use or zoning, issue building or development permits.


Current developed land use for the North Fork Edisto Watershed is 533.1 sq. miles. Based on current Geographic Information System (GIS) information (available at time of TMDL development) there are currently no SCDOT rest areas or other facilities located in the referenced watershed area.

The City of Orangeburg is currently a potentially designated Municipal Separate Storm Sewer Systems (MS4) community under NPDES Phase II Stormwater rules. Similar to regulated MS4s, potentially designated MS4 entities (as listed in 64 FR, P. 688837) or other unregulated MS4 communities located in the North Fork Edisto watershed may have the potential to contribute FC bacteria in stormwater runoff. If future MS4 permits are applicable to this watershed, then those discharges will be subject to the assumptions and requirements of the If future MS4 permits are applicable to this watershed, then those discharges will also become subject to the assumptions and requirements of the WLA portion of this TMDL. However, there may be industrial or construction activities going on at any time that could produce stormwater runoff.

Industrial facilities that have the potential to cause or contribute to a violation of a water quality standard are covered by the NPDES Storm Water Industrial General Permit (SCR000000). Construction activities are usually covered by the NPDES Storm Water Construction General Permit from DHEC (SCR100000). Where construction activities have the potential to affect water quality of a water body with a TMDL, the Storm Water Pollution Prevention Plan (SWPPP) for the site must address any pollutants of concern and adhere to any wasteload allocations in the TMDL. Note that there may be other stormwater discharges not covered under permits numbered SCS and SCR that occur in the referenced watershed. These activities are not subject to the WLA portion of the TMDL.

Figure 4. SCDOT Owned and Maintained Roads and Buildings

North Fork Edisto TMDL
Impaired Stations E-008, E-007B, E-099, E-035, E-092
Drainage Area = 728.16 sq. miles



3.2 Nonpoint Sources

Nonpoint source pollution is defined as pollution that is not released through pipes but rather originates from multiple sources over a relatively large area. Nonpoint sources can be divided into source activities related either to land or water use including failing septic tanks, improper animal-keeping practices, agriculture, forestry practices, wildlife and urban and rural runoff. Nonpoint source pollution is likely the major contributing factor to negatively impact water quality in this watershed. The Department recognizes that there may be wildlife, agricultural activities, grazing animals, septic tanks and/or other nonpoint source contributors located within unregulated areas (outside the permitted area) of the North Fork Edisto watershed. Nonpoint sources located in unregulated areas are subject to the LA and not the WLA component of the TMDL.

3.2.1 Wildlife

Wildlife (mammals and birds) can be a significant contributor of fecal coliform bacteria. Wildlife in this area typically includes deer, squirrels, raccoons, and other mammals as well as a variety of birds. A windshield survey demonstrated that ducks are active in the North Fork Edisto River. (picture, appendix C). According to a study conducted by SCDNR in 2008, there are an estimated 30-45 deer per square mile within Orangeburg County and Calhoun County and less than 15 deer per square mile in Aiken County and Lexington County (SCDNR 2008). Wildlife wastes are carried into nearby streams by runoff following rainfall or deposited directly in streams.

3.2.2 Agricultural Activities

Agricultural activities that involve livestock or animal wastes are potential sources of fecal coliform contamination of surface waters. Fecal matter can enter the waterway via runoff from the land or by direct deposition into the stream. Agricultural activities may represent a significant source in the North Fork Edisto watershed.

3.2.2.1 Agricultural Animal Facilities

Owners/operators of most commercial animal growing operations are required by SC Regulation 61-43, Standards for the Permitting of Agricultural Animal Facilities, to obtain permits for the handling, storage, treatment (if necessary) and disposal of the manure, litter and dead animals generated at their facilities (SCDHEC 2002). The requirements of R. 61-43 are designed to protect water quality; therefore, we have a reasonable assurance that facilities operating in compliance with this regulation should not contribute to downstream water quality impairments. SC currently does not have any confined animal feeding operations (CAFOs) under NPDES coverage; however, the State does have permitted animal feeding operations (AFOs) covered under R. 61-43. These permitted operations are not allowed to discharge to the North Fork Edisto and its tributaries and are covered under 'no discharge' (ND) permits. Discharges from these operations to the North Fork Edisto watershed are illegal and are subject to enforcement actions by SCDHEC.

There are currently 145 permitted active animal feeding operations (AFOs) in the North Fork Edisto watershed (Table 5) along with 119 associated spray fields. These facilities are routinely inspected for compliance. Permitted agricultural facilities that operate in compliance with their permit are not considered to be sources of impairment. Along with the AFOs there are numerous spray fields,

however during site visits it was observed that these are not directly contributing to the fecal coliform load of the watershed.

Table 5. Permitted Active Animal Feeding Operations within the North Fork Edisto Watershed

NPDES	FACILITY	OPERATION	CAFO_SIZE
ND0070921	ROLLIN MEADOWS FARM	POULTRY (LAYERS)	LARGE
ND0068845	GRAY POULTRY	POULTRY (BROILERS)	MEDIUM
ND0002828	MILLWOOD FARMS	PIGEONS	N/A
ND0082627	SEVEN OAKS FARM NO 1	POULTRY (BROILERS)	MEDIUM
ND0083593	LAIRD POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0079863	CASSIDY BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0065757	DOUGLAS POULTRY FARM	POULTRY (BROILERS)	LARGE
ND0010049	HAIR SWINE	SWINE	SMALL
ND0081370	CASTLEGATE	POULTRY (BROILERS)	MEDIUM
ND0085057	LUCAS POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0084212	KNIGHT BREEDER FARM	POULTRY (BREEDERS)	SMALL
ND0085456	RUSHTON POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0085006	WALLING POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0084760	WANG POULTRY	POULTRY (BROILERS)	LARGE
ND0085553	MCCARSON FARMS	POULTRY (BROILERS)	MEDIUM
ND0084778	JODEE COLLUM POULTRY	POULTRY (BROILERS)	LARGE
ND0077054	COLLUM POULTRY FACILITY	POULTRY (BROILERS)	MEDIUM
ND0082643	COLLUM POULTRY FACILITY	POULTRY (BROILERS)	MEDIUM
ND0085693	MAYDO FARMS	POULTRY (BROILERS)	LARGE
ND0084603	SUGAR HILL FARM	POULTRY (BROILERS)	LARGE
ND0084603	SUGAR HILL FARM	POULTRY (BROILERS)	LARGE
ND0085171	TRIPLE P FARMS	POULTRY (BROILERS)	MEDIUM
ND0073822	HALL STARRETT BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0082899	NORRIS FARMS (BREEDERS)	POULTRY (BREEDERS)	MEDIUM
ND0084671	NORTHCUTT FARMS	POULTRY (BROILERS)	MEDIUM
ND0074292	FLYING H FARM INC	POULTRY (BROILERS)	LARGE
ND0078531	OLIVER WEST POULTRY FARMS	POULTRY (BROILERS)	LARGE
ND0080012	PADGETT #1 BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0080021	PADGETT #2 BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0079359	PROVEAUX POULTRY FARM	POULTRY (BROILERS)	LARGE
ND0072541	HARTLEY POULTRY FARMS	POULTRY (BROILERS)	MEDIUM
ND0073989	HARTLEY POULTRY	POULTRY (BROILERS)	MEDIUM
ND0069779	BARR WAYNE/BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0082929	PADGETT FARMS	POULTRY (BROILERS)	MEDIUM
ND0082511	SHUMPERT POULTRY INC	POULTRY (BROILERS)	MEDIUM
ND0081302	J&J FARMS	POULTRY (BROILERS)	MEDIUM
ND0078000	M&M POULTRY	POULTRY (BROILERS)	LARGE
ND0070602	ALLEN KYZER POULTRY	POULTRY (BROILERS)	MEDIUM
ND0085243	LISA SHUMPERT FARMS	POULTRY (BROILERS)	MEDIUM
ND0084379	FARVIEW POULTRY FARM	POULTRY (BROILERS)	MEDIUM

ND0076384	FULMER POULTRY	POULTRY (BROILERS)	MEDIUM
ND0080764	SHUMPERT DAIRY	DAIRY	SMALL
ND0084743	RISH FARMS	POULTRY (BROILERS)	MEDIUM
ND0076155	COKER BRANCH FARM	POULTRY (BROILERS)	MEDIUM
ND0083534	SHUMPERT (DERWIN) POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0063606	BROWN POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0082678	BERRY POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0068012	GUNTER JODY BROILER FACILITY	POULTRY (BROILERS)	LARGE
ND0002062	WOOD BRUCE BROILER FACILITY	POULTRY (BROILERS)	LARGE
ND0072648	BARTL POULTRY	POULTRY (BROILERS)	SMALL
ND0014664	J&M ENTERPRISES	POULTRY (LAYERS)	SMALL
ND0069841	BOATWRIGHT BROILER FARM	POULTRY (BROILERS)	MEDIUM
ND0070131	FRICK DARRELL BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0060496	OSWALD POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0004766	ROY J FRICK & SONS INC	POULTRY (BROILERS)	LARGE
ND0080641	HARTLEY POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0066249	WALLY GANTT POULTRY	POULTRY (BROILERS)	SMALL
ND0074691	HALL BROILER FACILITY - MURIEL	POULTRY (BROILERS)	MEDIUM
ND0068641	NORRIS POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0081043	GUNTER STACKING SHED	STACKING SHED	N/A
ND0066427	PADGETT RANDY/POULTRY	POULTRY (BROILERS)	LARGE
ND0064041	PARADICE POULTRY FARM	POULTRY (BROILERS)	LARGE
ND0060895	COLUMBIA FARMS LEESVILLE	POULTRY (BROILERS)	MEDIUM
ND0066419	GUNTER ROY BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0002852	SHEALY POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0063207	PARADICE POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0073172	HALL POULTRY FARM #5	POULTRY (BROILERS)	SMALL
ND0085448	SAND RIDGE FARMS, LLC	POULTRY (BROILERS)	MEDIUM
ND0068926	HALLMAN POULTRY FACILITY - ROD	POULTRY (BROILERS)	MEDIUM
ND0082791	PINEY RIDGE FARM	POULTRY (BROILERS)	MEDIUM
ND0075639	HALL POULTRY FACILITY	POULTRY (BROILERS)	MEDIUM
ND0080420	HALLMAN POULTRY FACILITY - ROD	POULTRY (BROILERS)	MEDIUM
ND0078697	BRYANT MALCOLM/BROILER FACILITY	POULTRY (BROILERS)	SMALL
ND0069485	HARTLEY POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0069256	KYZER JIMMY/POULTRY FACILITY	POULTRY (BROILERS)	MEDIUM
ND0074454	HALLMAN BROILER FACILITY - MICHAEL	POULTRY (BROILERS)	MEDIUM
ND0084590	TRACY HALLMAN POULTRY FACILITY #2	POULTRY (BROILERS)	MEDIUM
ND0075167	JUDY'S POULTRY INC #1 & #2	POULTRY (BROILERS)	MEDIUM
ND0076171	HALLMAN BROILER FACILITY - TRACY	POULTRY (BROILERS)	MEDIUM

ND0005321	GUNTER SWINE	SWINE	SMALL
ND0083704	SAND HILL FARMS	POULTRY (BROILERS)	MEDIUM
ND0069299	SHADY OAK FARM	POULTRY (BROILERS)	MEDIUM
ND0069671	J&B POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0006271	RIKARD POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0070084	MARVIN GANTT POULTRY	POULTRY (BROILERS)	MEDIUM
ND0085120	FRICK (CAREY) BREEDER FARM	POULTRY (BREEDERS)	MEDIUM
ND0063649	FINK POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0070661	CORDER BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0073440	CHARLES ANDERSON POULTRY	POULTRY (BROILERS)	SMALL
ND0068985	SENN POULTRY FACILITY	POULTRY (BROILERS)	MEDIUM
ND0081906	KAMINER BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0014401	KEISLER POULTRY FACILITY	POULTRY (BROILERS)	SMALL
ND0062944	BOATWRIGHT JONES/BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0070840	DRAFTS BROILER FACILITY	POULTRY (BROILERS)	LARGE
ND0005126	A&A FARMS	POULTRY (BROILERS)	MEDIUM
ND0064912	CLAMP BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0083445	CAROL CLAMP POULTRY FARM #2	POULTRY (BROILERS)	MEDIUM
ND0063509	POPLAR SPRINGS POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0072907	WATKINS JUDY/BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0066931	LEAPHART EDDIE/BROILER FACILI	POULTRY (BROILERS)	LARGE
ND0065072	HALL RALPH BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0060798	CLAMP POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0067768	TROTTER'S FARM	POULTRY (BROILERS)	SMALL
ND0060631	CLAMP POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0072591	MCCARTHA POULTRY	POULTRY (BROILERS)	MEDIUM
ND0071102	J & A Poultry-formerly KEISLER POULTRY (LEASED) - SOX	POULTRY (BREEDERS)	SMALL
ND0064530	GUNTER RAYMOND BROILER FACILITY	POULTRY (BROILERS)	LARGE
ND0063274	CLAMP BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0068691	RICARD POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0068900	JONES POULTRY FACILITY	POULTRY (BROILERS)	SMALL
ND0082571	SHARPE FARMS INC	POULTRY (BROILERS)	LARGE
ND0084255	SPURS & FEATHERS POULTRY	POULTRY (BROILERS)	MEDIUM
ND0068667	POOLE POULTRY	POULTRY (BROILERS)	MEDIUM
ND0081779	RUCKER POULTRY FARM	POULTRY (BROILERS)	LARGE
ND0076163	POOLE POULTRY	POULTRY (BROILERS)	MEDIUM
ND0082538	STARNES POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0077046	BROWN POULTRY	POULTRY (BROILERS)	MEDIUM
ND0082325	PEBBLE CREEK ENTERPRISES	POULTRY (BROILERS)	MEDIUM
ND0077941	STARNES BREEDER FARM	POULTRY (BROILERS)	SMALL
ND0063878	PADGETT POULTRY FARM	POULTRY (BREEDERS & PULLETS)	MEDIUM
ND0063878	PADGETT POULTRY FARM	POULTRY (BREEDERS)	MEDIUM

		& PULLETS)	
ND0084999	PLATO KNEECE	POULTRY (BROILERS)	MEDIUM
ND0071773	WOODS POULTRY FARM	POULTRY (BROILERS)	MEDIUM
ND0081736	C&A BROILER FARMS	POULTRY (BROILERS)	MEDIUM
ND0084166	KNEECE FARM	POULTRY (BROILERS)	MEDIUM
ND0068365	JUDY'S POULTRY INC #3 & #4	POULTRY (BROILERS)	MEDIUM
ND0086754	WILLIAMSON POULTRY FARM	POULTRY (BROILERS)	LARGE
ND0069876	SMITHS POULTRY FARM	POULTRY (BROILERS)	SMALL
ND0070751	KIRKLAND POULTRY FACILITY	POULTRY (BROILERS)	LARGE
ND0082350	K & K FARMS	POULTRY (BROILERS)	MEDIUM
ND0073083	HOWARD POULTRY	POULTRY (BROILERS)	MEDIUM
ND0076317	EARGLE POULTRY	POULTRY (BROILERS)	SMALL
ND0072940	EARGLE POULTRY	POULTRY (BROILERS)	LARGE
ND0068543	EARGLE FARMS	POULTRY (BROILERS)	LARGE
ND0069116	FRICK RICKY BROILER FACILITY	POULTRY (BROILERS)	MEDIUM
ND0068683	TROY & ALLYSON SHELDON POULTRY FARM	POULTRY (PULLETS)	MEDIUM
ND0082198	BACKMAN LAND APPLICATION	LAND APPLIER	N/A
ND0063185	ROBINSON (DAVID) HOG FARM	SWINE	MEDIUM
ND0076180	DAVIS BROILER FACILITY	POULTRY (BROILERS)	LARGE
ND0069884	OSWALT WM & P/BROILER FACILIT	POULTRY (BROILERS)	LARGE
ND0073946	HALL BROILER FACILITY - STARRETT JR	POULTRY (BROILERS)	MEDIUM
ND0070238	HIGHPOINT FARMS	POULTRY (BROILERS)	LARGE
ND0017523	WALLY GANTT POULTRY	POULTRY (BROILERS)	MEDIUM
ND0078212	HOLLOW CREEK FARM	POULTRY (BROILERS)	MEDIUM
ND0072931	HOLLOW CREEK FARM	POULTRY (BROILERS)	MEDIUM

3.2.2.2 Grazing Animals

Livestock, especially cattle, are frequently major contributors of fecal coliform bacteria to streams. Cattle on average produce some 1 E+11 cfu/day per animal of fecal coliform bacteria (ASAE 1998). Grazing cattle and other livestock may contaminate streams with fecal coliform bacteria indirectly by runoff from pastures or directly by defecating into streams and ponds. The grazing of unconfined livestock (in pastures) is not regulated by SC DHEC. The United States Department of Agriculture's National Agricultural Statistics Service reported 12,737 cattle in Aiken County, 2,442 cattle in Calhoun County, 9,356 cattle in Lexington County, and 16,735 cattle in Orangeburg County in 2007 (USDA 2009). Pasture and crop land use within the North Fork Edisto watershed is estimated to be 163.73 square miles (104787 acres), or 22.5 %, which was derived from NLCD 2001. Pasture and crop land use within Aiken, Lexington, Calhoun and Orangeburg counties is estimated to be 3356.4 square miles (2148087 acres). By taking the ratio of the above land use the North Fork Edisto watershed is proportional to 48.8 % of all 4 counties' pasture/crop land use, assuming an even distribution across the counties. A windshield survey demonstrated that there are a number of cows and horses in the North Fork Edisto watershed. Direct loading by cattle or other livestock to surface waters within the watershed is likely to be a significant source of fecal coliform.

3.2.3 Leaking Sanitary Sewers and Illicit Discharges

Leaking sewer pipes and illicit sewer connections represent a direct threat to public health since they result in discharge of partially treated or untreated human wastes to the surrounding environment. Quantifying these sources is extremely speculative without direct monitoring of the source because the magnitude is directly proportional to the volume and its proximity to the surface water. Typical values of fecal coliform in untreated domestic wastewater range from 10^4 to 10^6 MPN/100mL (Metcalf and Eddy 1991).

Illicit sewer connections into storm drains result in direct discharges of sewage via the storm drainage system outfalls. Monitoring of storm drain outfalls during dry weather is needed to document the presence or absence of sewage in the drainage systems. There are currently no entities subject to any NPDES MS4 permit in the watershed.

3.2.4 Failing Septic Systems

Studies demonstrate that wastewater located four feet below properly functioning septic systems contain on average less than one fecal coliform bacteria organism per 100 mL (Ayres Associates 1993). Failed or non-conforming septic systems, however, can be a major contributor of fecal coliform to the North Fork Edisto and tributaries. Wastes from failing septic systems enter surface waters either as direct overland flow or via groundwater. Although loading to streams from failing septic systems is likely to be a continual source, wet weather events can increase the rate of transport of pollutants from failing septic systems because of the wash-off effect from runoff and the increased rate of groundwater recharge.

Within the North Fork Edisto watershed in Aiken, Lexington, Calhoun, and Orangeburg Counties it is estimated that there are 69,743 people living in 30,480 households (3,422 people living in 1,564 households in the Aiken County portion of the watershed, 29,031 people living in 11,887 households in the Lexington County portion of the watershed, 37,000 people living in 15,654 households in the Orangeburg County portion of the watershed, and 290 people living in 1,375 households in the Calhoun County portion of the watershed). This is based off of the 2000 U.S. Census. Of these a small part of the watershed near the cities of Leesville and Swansea in Lexington County, city of Aiken in Aiken County, and the city of Orangeburg in Orangeburg County is serviced by a community sewer system. This is comprised of 2,248 people living in 993 households (298 people in 144 households near Aiken, 4,262 people in 1907 households near Leesville and Swansea, and 12,188 people in 5,591 households near Orangeburg). There are no households serviced by a community sewer system in the Calhoun County portion of this watershed. Given that information and assuming one septic tank per household, it is estimated that there are 22,838 septic tanks within the entire North Fork Edisto watershed.

3.2.5 Urban Runoff

The City of Orangeburg is currently a potentially designated MS4 located in this watershed. Similar to regulated MS4s, potentially designated MS4 entities (as listed in FR 64, 235, P. 688837) or other unregulated MS4 communities located in the North Fork Edisto Watershed may have the potential to contribute fecal coliform bacteria in stormwater runoff. Dogs, cats, and other domesticated pets are the primary source of fecal coliform deposited on the urban landscape. There are also 'urban' wildlife, squirrels, raccoons, pigeons, and other birds, all of which contribute to the

fecal coliform load. A windshield survey demonstrated that many households have dogs and/or cats, many of which are free roaming.

Roads, facilities and/or properties owned and/or operated by the South Carolina Department of Transportation (SCDOT) is/are currently covered under NPDES MS4 SCS040001, hence covered under the WLA (waste load allocation) portion of this TMDL. There may be other non-regulated roads (county roads) within the watershed that could contribute to FC loading within the North Fork Edisto watershed. Runoff from properties including but not limited to ditches, culverts and right of ways may have the potential to contribute or convey fecal coliform loading.

4.0 LOAD-DURATION CURVE METHOD

The load-duration curve method was developed as a means of incorporating natural variability, uncertainty, and risk assessment into TMDL development (Bonta and Cleland 2003). The analysis is based on the range of hydrologic conditions for which there are appropriate water quality data. The load-duration curve method uses the cumulative frequency distribution of stream flow and pollutant concentration data to estimate existing and TMDL loads for a water body. Development of the load-duration curve is described in this chapter.

The load-duration curve method depends on an adequate period of record for flow data. Gauge 02173500, North Fork Edisto River at Orangeburg, was used. This gauge began recording daily flows in 1970 and provides the flow data required to establish flow duration curves at each of the impaired stations.

Flow data for a ten year period (1996-2006) were used to establish flow duration curves. The records for this period were complete (i.e., no missing dates) for the North Fork Edisto River gauge. The flow records were used to estimate flow at the impaired monitoring stations.

Drainage areas of each sampling station were delineated using USGS topographic maps and ArcMap software. The cumulative area drained was calculated and used to estimate flow based on the ratio of the monitoring station drainage area to the downstream USGS gauge. For example, the USGS North Fork Edisto gauge records flow from 683 square miles (sq mi). The cumulative drainage area at monitoring stations E-035, E-092, E-007B, and E-008 is approximately 471,679, or 690% of the area drained at the North Fork Edisto River gauge. Mean daily flow for the monitoring locations was assumed to be 690 % of the daily flow at the North Fork Edisto gauge.

Flow duration curves were developed by ranking flows from highest to lowest and calculating the probability of occurrence (presented as a percentage or duration interval), where zero corresponds to the highest flow. The duration interval can be used to determine the percentage of time a given flow is achieved or exceeded, based on the period of record. Flow duration curves were divided into five hydrologic condition categories (High Flows, Moist Conditions, Mid-Range, Dry Conditions and Low Flows). Categorizing flow conditions can assist in determining which hydrologic conditions result in the greatest number of exceedences. A high number of exceedences under dry conditions might indicate a point source or illicit connection issue, whereas moist conditions may indicate nonpoint sources. Data within the High Flow and Low Flow categories are generally not used in the development of a TMDL due to their infrequency.

A target load-duration curve was created by calculating the allowable load using daily flow, the fecal coliform WQS concentration and a unit conversion factor. The water quality target was set at 380 cfu/100ml for the instantaneous criterion, which is five percent lower than the water quality criteria of 400 cfu/100ml. A five percent explicit Margin of Safety (MOS) was reserved from the water quality criteria in developing target load-duration curves. The load-duration curve for station E-035 is presented in Figure 5.


For the load duration curve, the independent variable (X-Axis) represents the percentage of estimated flows greater than value x. The dependent variable (Y-Axis) represent the fecal coliform loading at each estimated flow expressed in terms of colony forming units per day (cfu/day). In each defined flow interval, existing and target loadings were calculated by the following equations:

$$\text{Existing Load} = \text{Mid-Point Flow in Each Hydrologic Category} \times 90^{\text{th}} \text{ Percentile Fecal Coliform Concentration} \times 10000$$

$$\text{Target Load} = \text{Mid-Point Flow in Each Hydrologic Category} \times 380 \text{ (WQ criterion minus a 5\% MOS)} \times 10000$$

$$\text{Percent Reduction} = (\text{Existing Load} - \text{Target Load}) / \text{Existing Load}$$

Figure 5. Load Duration Curve for North Fork Edisto Station E-035



Instantaneous loads for each of the impaired stations were calculated. Measured fecal coliform concentrations from 2001- 2008 were multiplied by measured (or estimated flow based on drainage area) flow on the day of sampling and a unit conversion factor. These data were plotted on the load-duration graph based on the flow duration interval for the day of sampling. Samples above the

target line are violations of the WQS while samples below the line are in compliance (Figure 4). Only the instantaneous water quality criterion was targeted because there is insufficient data to evaluate against the 30-day geometric mean.

An existing load was determined for each hydrologic category for the TMDL calculations. The 90th percentile of measured fecal coliform concentration within each hydrologic category was multiplied by the flow at each category midpoint (i.e., flow at the 25% duration interval for the Moist Conditions, 50% interval for Mid-Range, and 75% for Dry Condition). Existing loads are plotted on the load-duration curves presented in Figure 4. These values were compared to the target load (which includes an explicit 5% MOS) at each hydrologic category midpoint to determine the percent load reduction necessary to achieve compliance with the WQS. This TMDL assumes that if the highest percent reduction is achieved then the WQS will be attained under all flow conditions.

5.0 DEVELOPMENT OF TOTAL MAXIMUM DAILY LOAD

A total maximum daily load (TMDL) for a given pollutant and water body is comprised of the sum of individual wasteload allocations (WLAs) for point sources, and load allocations (LAs) for both nonpoint sources and natural background levels. In addition, the TMDL must include a margin of safety (MOS), either implicitly or explicitly, to account for the uncertainty in the relationship between pollutant loads and the quality of the receiving water body. Conceptually, this definition is represented by the equation:

$$TMDL = \sum WLAs + \sum LAs + MOS$$

The TMDL is the total amount of pollutant that can be assimilated by the receiving water body while still achieving compliance with WQS. In TMDL development, allowable loadings from all pollutant sources that cumulatively amount to no more than the TMDL must be established and thereby provide the basis to establish water quality-based controls.

For most pollutants, TMDLs are expressed as a mass load (e.g., kilograms per day). For bacteria, however, TMDLs are expressed in terms of number (#), colony forming units (cfu), organism counts (or resulting concentration), or MPN (Most Probable Number), in accordance with 40 CFR 130.2(i).

5.1 Critical Conditions

This TMDL is based on the flow recurrence interval between 10% and 90% and excludes extreme high and low flow conditions; flows that are characterized as ‘Low’ or ‘High’ were not included in the analysis. The critical condition for each monitoring station is identified as the flow condition requiring the largest percent reduction, within the 10-90% duration intervals. Critical conditions for the North Fork Edisto watershed pathogen impaired segments are listed in Table 6. These data indicate that for stations E-035, E-007B, E-099 and E-008 moist weather conditions results in larger bacteria loads and is therefore the critical condition. For station E-092, the critical condition is dry.

5.2 Existing Load

An existing load was determined for each hydrologic category for the TMDL calculations as described in Section 4.0 of this TMDL. The existing load under the critical condition, described in

Section 5.1 above was used in the TMDL calculations. Loadings from all sources are included in this value: wildlife, cattle-in-streams, urban run-off as well as failing septic systems. The existing load for stations E-035, E-092, E-007B, E-099 and E-008 in the North Fork Edisto River watershed is provided in Appendix C.

Table 6. Percent Reduction Necessary to Achieve Target Load by Hydrologic Category.

Station	Waterbody	Moist Conditions	Mid-Range Flow	Dry Conditions
E-035	Bull Swamp Creek	71%	NRN	NRN
E-092	North Fork Edisto	NRN	NRN	5%
E-007B	North Fork Edisto	30%	NRN	NRN
E-008	North Fork Edisto	19 %	NRN	NRN
E-099	North Fork Edisto	5%	NRN	NRN

Highlighted cells indicate critical condition.

NRN = no reduction needed. Existing load below target load.

5.3 Wasteload Allocation

The wasteload allocation (WLA) is the portion of the TMDL allocated to NPDES-permitted point sources (USEPA 1991). Note that all illicit dischargers, including SSOs, are illegal and not covered under the WLA of this TMDL.

5.3.1 Continuous Point Source

There is currently one active NPDES-permitted domestic discharger of FC bacteria in the North Fork Edisto watershed. Future continuous discharges are required to meet the prescribed loading for the pollutant of concern based on permitted flow and an allowable permitted maximum concentration of 400cfu/100mL. To determine the waste load allocation (WLA) for the permitted sanitary discharger, the average monthly permitted flow for the facility was multiplied by the instantaneous WQS (400 cfu/100 mL) and a unit conversion factor. The WLA for the discharger, based on a permitted daily maximum of 400 cfu/100ml, is presented in Table 7. For the Edisto High School WWTP the waste load allocation was determined to be 2.57 E+8 based on a permitted average monthly flow of 5.1 MGD.

Table 7. Average Monthly Permitted Flow and WLAs for the NPDES Wastewater Discharges in the North Fork Edisto Watershed

Impaired Station	Facility Name	Permit #	Average Monthly Permitted Flow (MGD)	WLA (#/day)
E-008	Edisto High School	SC0040185	5.1	2.57E+8

5.3.2 Non-Continuous Point Sources

Non-continuous point sources include all NPDES-permitted stormwater discharges, including current and future MS4s, construction and industrial stormwater discharges covered under permits numbered SCS & SCR and regulated under SC Water Pollution Control Permits Regulation 122.26(b)(14) & 15 (SCDHEC 2003). Illicit discharges, including SSOs, are not covered under any NPDES permit and are subject to enforcement mechanisms. All areas defined as “Urbanized Area” by the US Census are required under the NPDES Phase II Stormwater Regulations to obtain a permit for the discharge of stormwater.

Waste load allocations for stormwater discharges are expressed as a percentage reduction instead of a numeric loading due to the uncertain nature of stormwater discharge volumes and recurrence intervals. Stormwater discharges are required to meet the percentage reduction or the existing instream standard for the pollutant of concern. The percent reduction is based on the maximum percent reduction (critical condition) within any hydrologic category necessary to achieve target conditions. Table 8 presents the reduction needed for the impaired segment. The reduction percentages in this TMDL also apply to the fecal coliform waste load attributable to those areas of the watershed which are covered or will be covered under NPDES MS4 permits. Compliance by an entity with responsibility for the MS4, with the terms of its individual MS4 permit may fulfill any obligations it has towards implementing this TMDL.

As appropriate information is made available to further define the pollutant contributions for the permitted MS4, an effort can be made to revise these TMDLs. This effort will be initiated as resources permit and if deemed appropriate by the Department. For the Department to revise these TMDLs the following information should be provided, but not limited to:

1. An inventory of service boundaries of the MS4 covered in the MS4 permit, provided as ARCGIS compatible shape files.
2. An inventory of all existing and planned stormwater discharge points, conveyances, and drainage areas for the discharge points, provided as ARCGIS compatible shape files. If drainage areas are not known, any information that would help estimate the drainage areas should be provided. The percentage of impervious surface within the MS4 area should also be provided.
3. Appropriate and relevant data should be provided to calculate individual pollutant contributions for the MS4 permitted entities. At a minimum, this information should include precipitation, water quality, and flow data for stormwater discharge points.

Compliance with terms and conditions of existing and future NPDES sanitary and stormwater permits (including all construction, industrial and MS4) may effectively implement the WLA and demonstrate consistency with the assumptions and requirements of the TMDL. However, the Department recognizes that SCDOT is not a traditional MS4 in that it does not possess statutory taxing or enforcement powers. SCDOT does not regulate land use or zoning, issue building or development permits.

Table 8. Percent Reduction Necessary to Achieve Target Load.

Station	Waterbody	% Reduction
E-035	Bull Swamp Creek	71 %
E-092	North Fork Edisto	5 %
E-007B	North Fork Edisto	30%
E-008	North Fork Edisto	19%
E-099	North Fork Edisto	5%

5.4 Load Allocation

The Load Allocation applies to the nonpoint sources of fecal coliform bacteria and is expressed both as a load and as a percent reduction. The load allocation is calculated as the difference between the target load under the critical condition and the point source WLA. The load allocation for each station is listed in Table Ab-1 and Table 9. The City of Orangeburg is a potentially designated MS4 located in this watershed and is currently subject to the LA component of this TMDL. There may also be other unregulated MS4s located in the watershed that are subject to the LA component of this TMDL. At such time that the referenced entities, or other future unregulated entities become regulated NPDES MS4 entities and subject to applicable provisions of SC Regulation 61-68 D, they will be required to meet load reductions prescribed in the WLA component of the TMDL. This also applies to future discharges associated with industrial and construction activities that will be subject to SC R. 122.26(b)(14) & (15) (SCDHEC 2003).

5.5 Seasonal Variability

Federal regulations require that TMDLs take into account the seasonal variability in watershed loading. The variability in this TMDL is accounted for by using a 10-year hydrological data set and 1-year water quality sampling data set, which includes data collected from all seasons.

5.6 Margin of Safety

The margin of safety (MOS) may be explicit and/or implicit. The explicit margin of safety is 5% of the TMDL or 20 counts/100mL of the instantaneous criterion of 400 cfu/100 mL (380 cfu/100mL). Target loads are therefore 95% of the assimilative capacity (TMDL) of the waterbody. The MOS is expressed as the value calculated from the critical condition defined in Section 5.1 and is the difference between the TMDL and the sum of the WLA and LA. The calculated values of the MOS for each station are given in Table 9.

5.7 TMDL

For most pollutants, TMDLs are expressed as a mass load (e.g., kilograms per day). For bacteria, however, TMDLs are expressed in terms of cfu or organism counts (or resulting concentration), in accordance with 40 CFR 130.2(l). Only the instantaneous water quality criterion was targeted because there is insufficient data to evaluate against the 30-day geometric mean. The target load is defined as the load (from point and nonpoint sources) minus the MOS that a stream segment can

receive while meeting the WQS. The TMDL value is the median target load within the critical condition (i.e., the middle value within the hydrologic category that requires the greatest load reduction) plus WLA and MOS. Values for each component of the TMDL for the impaired segments of the North Fork Edisto watershed are provided in Table 9.

While TMDL development was primarily based on instantaneous water quality criterion, terms and conditions of NPDES permits for continuous discharges require facilities to demonstrate compliance with both geometric mean and instantaneous water quality criteria for fecal coliform bacteria in treated effluent. NPDES permits for continuous dischargers require data collection sufficient to monitor for compliance of both criteria at the point of outfall.

Table 9 indicates the percentage reduction or water quality standard for each impaired station of the North Fork Edisto TMDL. Note that all future NPDES-permitted stormwater discharges will also be required to meet the prescribed percentage reductions, or the water quality standard. It should be noted that in order to meet the WQS for FC bacteria, prescribed load reductions must be targeted from all sources, including NPDES permitted and nonpoint sources.

Based on the available information at this time, the portion of the watershed that drains directly to a regulated MS4 and that which drains through the unregulated MS4 has not been clearly defined within the MS4 jurisdictional area. Loading from both types of sources (regulated and unregulated) typically occurs in response to rainfall events, and discharge volumes as well as recurrence intervals are largely unknown. Therefore, the regulated MS4 is assigned the same percent reduction as the non-regulated sources in the watershed. Compliance with the MS4 permit in regards to this TMDL document is determined at the point of discharge to waters of the state. The regulated MS4 entity is only responsible for implementing the TMDL WLA in accordance with their MS4 permit requirements and is not responsible for reducing loads prescribed as LA in this document.

Table 9. TMDL Components for the Fecal Coliform Impaired Segments in the North Fork Edisto Watershed. Loads are expressed as colony forming units (cfu) per day.

Station	Existing Load (cfu/day)	TMDL (cfu/day)	MOS (cfu/day)	Wasteload Allocation (WLA)		Load Allocation (LA)	
				Continuous Sources ¹ (cfu/day)	Non-continuous Sources ^{2,3,4} (% Reduction)	LA (cfu/day)	% Reduction to Meet LA ³
E-035	7.62E+12	2.79E+12	1.39E+11	NA	71%	2.65E+12	71 %
E-092	3.15E+12	3.86E+12	1.93E+11	NA	5%	3.67E+12	5%
E-007 B	2.77E+11	2.04E+11	1.02E+10	NA	30%	1.94E+11	30%
E-008	6.25E+12	5.34E+12	2.67E+11	2.57E+8	19%	5.07E+12	19%
E-099	7.11E+12	7.11E+12	3.56E+12	NA	5%	6.76E+12	5%



1. WLAs are expressed as a daily maximum; NA = not applicable, no point sources. Continuous discharges are required to meet the prescribed loading or the existing instream standard for the pollutant of concern. Loadings were developed based upon permitted flow and an allowable permitted maximum concentration of 400cfu/100ml.

2. Percent reduction applies to all NPDES-permitted stormwater discharges, including current and future MS4, construction and industrial discharges covered under permits numbered SCS & SCR. Stormwater discharges are expressed as a percentage reduction due to the uncertain nature of stormwater discharge volumes and recurrence intervals. Stormwater discharges are required to meet percentage reduction or the existing instream standard for pollutant of concern in accordance with their NPDES permit.
3. Percent reduction applies to existing instream load.
4. By implementing the best management practices that are prescribed in either the SCDOT annual SWMP or the SCDOT MS4 permit to address fecal coliform, the SCDOT will comply with this TMDL and its applicable WLA to the maximum extent practicable (MEP) as required by its MS4 permit

Figure 6. Percent Reductions

Percent Reductions Needed at Each Reach

- Reach 1 = 5 %**
- Reach 2 = 71 %**
- Reach 3 = 5 %**
- Reach 4 = 30 %**
- Reach 5 = 19 %**



6.0 Implementation

The implementation of both point (WLA) and non-point (LA) source components of the TMDL are necessary in order to meet water quality standard. Using existing authorities and mechanisms, an implementation plan providing information on how point and non point sources of pollution are being abated or may be abated in order to meet water quality standards is provided. Sections 6.1.1-6.1.7 presented below correspond with sections 3.1.1-3.2.5 of the source assessment presented in the TMDL document. As the implementation strategy progresses, DHEC will continue to monitor the effectiveness of implementation measures and evaluate water quality where deemed appropriate.

Point sources are discernible, confined, and discrete conveyances of pollutants to a water body including but not limited to pipes, outfalls, channels, tunnels, conduits, man-made ditches, etc. The Clean Water Act's primary point source control program is the National Pollutant Discharge Elimination System (NPDES). Point sources can be broken down into continuous and non-continuous point sources. Some examples of a continuous point source are wastewater treatment facilities (WWTF) and industrial facilities. Non-continuous point sources are related to stormwater and include municipal separate storm sewer systems (MS4), construction activities, etc. Current and future NPDES discharges in the referenced watershed are required to comply with the load reductions prescribed in the wasteload allocation (WLA).

Nonpoint source pollution originates from multiple sources over a relatively large area. It is diffuse in nature and indistinct from other sources of pollution. It is generally caused by the pickup and transport of pollutants from rainfall moving over and through the ground. Nonpoint sources of pollution may include, but are not limited to: wildlife, agricultural activities, illicit discharges, failing septic systems, and urban runoff. Nonpoint sources located in unregulated portions of the watershed are subject to the load allocation (LA) and not the WLA of the TMDL document.

South Carolina has several tools available for implementing the non-point source component of this TMDL. The *Implementation Plan for Achieving Total Maximum Daily Load Reductions From Nonpoint Sources for the State of South Carolina* (SCDHEC 1998) document is one example. Another key component for interested parties to control pollution and prevent water quality degradation in the watershed would be the establishment and administration of a program of Best Management Practices (BMPs). Best management practices may be defined as a practice or a combination of practices that have been determined to be the most effective, practical means used in the prevention and/or reduction of pollution.

Interested parties (local stakeholder groups, universities, local governments, etc.) may be eligible to apply for CWA §319 grants to install BMPs that will implement the LA portion of this TMDL and reduce nonpoint source FC loading to the North Fork Edisto and its tributaries. Congress amended the Clean Water Act (CWA) in 1987 to establish the Section 319 Nonpoint Source Management Program. Under Section 319, States receive grant money to support a wide variety of activities including the restoration of impaired waters. TMDL implementation projects are given highest priority for 319 funding. CWA §319 grants are not available for implementation of the WLA component of this TMDL nor within the MS4 jurisdictional boundary. Additional resources are provided in Section 7.0 of this TMDL document.

SCDHEC will also work with the existing agencies in the area to provide nonpoint source education in the North Fork Edisto watershed. Local sources of nonpoint source education and assistance

include the Natural Resource Conservation Service (NRCS), the Clemson University Cooperative Extension Service, and the South Carolina Department of Natural Resources.

The Department recognizes that **adaptive management/implementation** of this TMDL might be needed to achieve the water quality standard and we are committed towards targeting the load reductions to improve water quality in the North Fork Edisto Watershed. As additional data and/or information becomes available, it may become necessary to revise and/or modify the TMDL target accordingly.

6.1 Implementation Strategies

The strategies presented in this document for implementation of the referenced TMDL are not inclusive and are to be used only as guidance. The strategies are informational suggestions which may or may not lead to the required load reductions being met for the referenced watershed while demonstrating consistency with the assumptions and requirements of the TMDL. Application of certain strategies provided within may be voluntary and they are not a substitute for actual NPDES permit conditions.

Point Sources

6.1.1 Continuous Point Sources

Continuous point source WLA reductions will be implemented through NPDES permits. Existing and future continuous discharges are required to meet the prescribed loading for the pollutant of concern and demonstrate consistency with the assumptions and requirements of the TMDL. Loadings are developed based upon permitted flow and assume an allowable permitted maximum concentration of 400cfu/100ml.

6.1.2 Non-Continuous Point Sources

An iterative BMP approach as defined in the general storm water NPDES MS4 permit is expected to provide significant implementation of the WLA. Permit requirements for implementing WLAs in approved TMDLs will vary across waterbodies, discharges, and pollutant(s) of concern. The allocations within a TMDL can take many different forms – narrative, numeric, specific BMPs – and may be complimented by other special requirements such as monitoring.

The level of monitoring necessary, deployment of structural and non-structural BMPs, evaluation of BMP performance, and optimization or revisions to the existing pollutant reduction goals of the SWMP or any other plan is TMDL and watershed specific. Hence, it is expected that NPDES permit holders evaluate their existing SWMP or other plans in a manner that would effectively address implementation of this TMDL with an acceptable schedule and activities for their permit compliance. The Department staff (permit writers, TMDL project managers, and compliance staff) is willing to assist in developing or updating the referenced plan as deemed necessary. Please see Appendix F which provides additional information as it relates to evaluating the effectiveness of an MS4 Permit as it related to compliance with approved TMDLs. For SCDOT, existing and future NPDES MS4 permittees, compliance with terms and conditions of its NPDES permit is effective implementation of the WLA to the Maximum Extent Practicable. For existing and future NPDES construction and Industrial stormwater permittees, compliance with terms and conditions of its permit is effective implementation of the WLA.

The Department acknowledges that progress with the assumptions and requirements of the TMDL by MS4s is expected to take one or more permit iteration. Achieving the WLA reduction for the TMDL may constitute MS4 compliance with its SWMP, provided the MEP definition is met, even where the numeric percent reduction may not be achieved in the interim.

Regulated MS4 entities are required to develop a SWMP that includes the following: public education, public involvement, illicit discharge detection & elimination, construction site runoff control, post construction runoff control, and pollution prevention/good housekeeping. These measures are not exhaustive and may include additional criterion depending on the type of NPDES MS4 permit that applies. These examples are recognized as acceptable stormwater practices and may be applied to unregulated MS4 entities or other interested parties in the development of a stormwater management plan.

An informed and knowledgeable community is crucial to the success of a stormwater management plan (USEPA, 2005). MS4 entities may implement a public education program to distribute educational materials to the community, or conduct equivalent outreach activities about the impacts of stormwater discharges on local waterbodies and the steps that can be taken to reduce stormwater pollution. Some appropriate BMPs may be brochures, educational programs, storm drain stenciling, stormwater hotlines, tributary signage, and alternative information sources such as web sites and bumper stickers (USEPA, 2005).

The public can provide valuable input and assistance to a MS4 program and they may have the potential to play an active role in both development and implementation of the stormwater program where deemed appropriate. There are a variety of practices that can involve public participation such as public meetings/citizens panels, volunteer water quality monitoring, volunteer educators, community clean-ups, citizen watch groups, and “Adopt a Storm Drain” programs which encourage individuals or groups to keep storm drains free of debris and monitor what is entering local waterways through storm drains (USEPA, 2005).

Illicit discharge detection and elimination efforts are also necessary. Discharges from MS4s often include wastes and wastewater from non-stormwater sources. These discharges enter the system through either direct connections or indirect connections. The result is untreated discharges that contribute high levels of pollutants, including heavy metals, toxics, oil and grease, solvents, nutrients, viruses, and bacteria to receiving waterbodies (USEPA, 2005). Pollutant levels from these illicit discharges have been shown in EPA studies to be high enough to significantly degrade receiving water quality and threaten aquatic, wildlife, and human health. MS4 entities may have a storm sewer system map which shows the location of all outfalls and to which waters of the US they discharge to. If not already in place, an ordinance prohibiting non-stormwater discharges into MS4 with appropriate enforcement procedures may also be developed. Entities may also have a plan for detecting and addressing non-stormwater discharges. The plan may include locating problem areas through infrared photography, finding the sources through dye testing, removal/correction of illicit connections, and documenting the actions taken to illustrate that progress is being made to eliminate illicit connections and discharges.

A program might also be developed to reduce pollutants in stormwater runoff to their MS4 from construction activities. An ordinance or other regulatory mechanism may exist requiring the implementation of proper erosion and sediment controls on applicable construction sites. Site plans

should be reviewed for projects that consider potential water quality impacts. It is recommended that site inspections should be conducted and control measures enforced where applicable. A procedure might also exist for considering information submitted by the public (USEPA, 2005). For information on specific BMPs please refer to the SCDHEC Stormwater Management BMP Handbook online at: http://www.scdhec.com/environment/ocrm/pubs/docs/SW/BMP_Handbook/Erosion_prevention.pdf

Post-construction stormwater management in areas undergoing new development or redevelopment is recommended because runoff from these areas has been shown to significantly affect receiving waterbodies. Many studies indicate that prior planning and design for the minimization of pollutants in post-construction stormwater discharges is the most cost-effective approach to stormwater quality management (USEPA, 2005). Strategies might be developed to include a combination of structural and/or non-structural BMPs. An ordinance or other regulatory mechanism may also exist requiring the implementation of post-construction runoff controls and ensuring their long term-operation and maintenance. Examples of non-structural BMPs are planning procedures and site-based BMPs (minimization of imperviousness and maximization of open space). Structural BMPs may include but are not limited to stormwater retention/detention BMPs, infiltration BMPs (dry wells, porous pavement, etc.), and vegetative BMPs (grassy swales, filter strips, rain gardens, artificial wetlands, etc.).

Pollution prevention/good housekeeping is also a key element of stormwater management programs. Generally this requires the MS4 entity to examine and alter their actions to ensure reductions in pollution are occurring. This could also result in a reduction of costs for the MS4 entity. It is recommended that a plan be developed to prevent or reduce pollutant runoff from municipal operations into the storm sewer system and it is encouraged to include employee training on how to incorporate pollution prevention/good housekeeping techniques. To minimize duplication of effort and conserve resources, the MS4 operator can use training materials that are available from EPA or relevant organizations (USEPA, 2005).

MS4 communities are encouraged to utilize partnerships when developing and implementing a stormwater management program. Watershed associations, educational entities, and state, county, and city governments are all examples of possible partners with resources that can be shared. For additional information on partnerships contact the SCDHEC Watershed Manager for the waterbody of concern online at: <http://www.scdhec.gov/environment/water/shed/contact.htm> For additional information on stormwater discharges associated with MS4 entities please see the USEPA NPDES website online at http://cfpub.epa.gov/npdes/home.cfm?program_id=6 for information pertaining to the National Menu of BMPs, Urban BMP Performance Tool, Outreach Documents, etc.

Nonpoint Sources

6.1.3 Wildlife

Suggested forms of implementation for wildlife will vary widely due to geographic location and species. During a source assessment it was noted that waterfowl were present. Deterrents could be used to keep waterfowl away from lawns in close proximity to surface waters. These include non-toxic sprays, decoys, kites, noisemakers, scarecrows, and plastic owls. Homeowners should be educated on the impacts of feeding wildlife or planting food plots in close proximity to surface waters. Please check local and federal laws before applying deterrents or harassing wildlife.

Additional information may be obtained from the “Managing Pet and Wildlife Waste to Prevent Contamination of Drinking Water” bulletin provided by USEPA (2001).

6.1.4 Agricultural Activities

Suggested forms of implementation for agricultural activities will vary based on the activity of concern. Agricultural BMPs can be vegetative, structural or management oriented. When selecting BMPs, it is important to keep in mind that nonpoint source pollution occurs when a pollutant becomes available, is detached and then transported to nearby receiving waters. Therefore, for BMPs to be effective the transport mechanism of the pollutant, fecal coliform, needs to be identified.

There are currently 152 animal feeding operations (AFO) located in the North Fork Edisto watershed. The following are BMP suggestions for these farms.

Installing fencing along the streams within the watershed and providing an alternative water source where livestock are present would eliminate direct contact with the streams. If fencing is not feasible, it has been shown that installing water troughs within a pasture area reduced the amount of time livestock spent drinking directly from streams by 92% (ASABE 1997). An indirect result of this was a 77% reduction in stream bank erosion by providing an alternative to accessing the stream directly for water supply. It was also noted during a windshield survey that several cow pastures had numerous amounts of manure. A manure storage facility would not only help water quality by minimizing the amount of FC that could be flushed into the creek after a rain, but it would also allow farmers to purchase little to no fertilizer and save money. The manure could be applied to crops when they will readily use it.

For row crop farms in the referenced watershed, many common practices exist to reduce FC contributions. Unstabilized soil directly adjacent to surface waters can contribute to FC loading during periods of runoff after rain events. Agricultural field borders and filter strips (vegetative buffers) can provide erosion control around the border of planted crop fields. These borders can provide food for wildlife, may possibly be harvested (grass and legume), and also provide an area where farmers can turn around their equipment (SCDNR 1997). A study conducted in 1998 by the American Society of Agricultural and Biological Engineers (ASABE) has shown that a vegetative buffer measuring 6.1 meters in width can reduce fecal runoff concentrations from 2.0E+7 to an immeasurable amount once filtered through the buffer. A buffer of this width was also shown to reduce phosphorous and nitrogen concentrations by 75%.

The agricultural BMPs listed above are a sample of the many accepted practices that are currently available. Many other techniques such as conservation tillage, responsible pest management, and precision agriculture also exist and may contribute to an improvement in overall water quality in the watershed. Education should be provided to local farmers on these methods as well as acceptable manure spreading and holding (stacking sheds) practices.

For additional information on accepted agricultural BMPs you can obtain a copy of the “Farming for Clean Water in South Carolina” handbook by contacting Clemson University Cooperative Extension Service at (864) 656-1550. In addition, Clemson Extension Service offers a ‘Farm-A-Syst’ package to farmers. Farm-A-Syst allows the farmer to evaluate practices on their property and determine the nonpoint source impact they may be having. It recommends best management

practices (BMPs) to correct nonpoint source problems on the farm. You can access Farm-A-Syst by going onto the Clemson Extension Service website: <http://www.clemson.edu/waterquality/FARM.HTM>

NRCS provides financial and technical assistance to help South Carolina landowners address natural resource concerns, promote environmental quality, and protect wildlife habitat on property they own or control. The cost-share funds are available through the Environmental Quality Incentives Program (EQIP). EQIP helps farmers improve production while protecting environmental quality by addressing such concerns as soil erosion and productivity, grazing management, water quality, animal waste, and forestry concerns. EQIP also assists eligible small-scale farmers who have historically not participated in or ranked high enough to be funded in previous sign ups. Please visit www.sc.nrcs.usda.gov/programs/ for more information, including eligibility requirements.

Also available through NRCS, the Grassland Reserve Program (GRP) is a voluntary program offering landowners the opportunity to protect, restore and enhance grasslands on their property. NRCS and the Farm Service Agency (FSA) coordinate implementation of the GRP, which helps landowners restore and protect grassland, rangeland, pastureland, shrubland and certain other lands and provides assistance for rehabilitating grasslands. The program will conserve vulnerable grasslands from conversion to cropland or other uses and conserve valuable grasslands by helping maintain viable grazing operations. A grazing management plan is required for participants. NRCS has further information on their website for the GRP as well as additional programs such as the Conservation Reserve Program, Conservation Security Program, Farm and Ranch Lands Protection Program, etc. You can visit the NRCS website by going to: www.sc.nrcs.usda.gov/programs/

6.1.5 Leaking Sanitary Sewers and Illicit Discharges

Leaking sanitary sewers and illicit discharges, although illegal and subject to enforcement, may be occurring in the watershed at any time. It should be recognized that these activities may occur in unregulated portions of the watershed. Due to the high concentration of pollutant loading that is generally associated with these discharges, their detection may provide a substantial improvement in overall water quality in the North Fork Edisto watershed. Detection methods may include, but are not limited to: dye testing, air pressure testing, static pressure testing, and infrared photography.

SCDHEC recognizes illicit discharge detection and elimination activities are conducted by MS4 entities as pursuant to compliance with existing MS4 permits. Note that these activities are designed to detect and eliminate illicit discharges that may contain FC bacteria. It is the intent of SCDHEC to work with the MS4 entities to recognize FC load reductions as they are achieved. SCDHEC acknowledges that these efforts to reduce illicit discharges and SSOs are ongoing and some reduction may already be accountable (i.e. load reductions occurring during TMDL development process). Thus, the implementation process is an iterative and adaptive process. Regular communication between all implementation stakeholders will result in successful remediation of controllable sources over time. As recreational uses are restored, SCDHEC will recognize efforts of implementers where their efforts can be directly linked to restoration.

6.1.6 Failing Septic Systems

A septic system, also known as an onsite wastewater system, is defined as failing when it is not treating or disposing of sewage in an effective manner. The most common reason for failure is improper maintenance by homeowners. Untreated sewage water contains disease-causing bacteria and viruses, and well as unhealthy amounts of nitrate and other chemicals. Failed septic systems can allow untreated sewage to seep into wells, groundwater, and surface water bodies, where people get their drinking water and recreate. Pumping a septic tank is probably the single most important thing that can be done to protect the system. If the buildup of solids in the tanks becomes too high and solids move to the drainfield, this could clog and strain the system to the point where a new drainfield will be needed.

The Office of Coastal Resource Management (OCRM) has created a toolkit for homeowners and local governments which includes tips for maintaining their systems. These septic system Do's and Don't's are as follows:

Septic System Do's and Don'ts from SCDHEC Office of Coastal Resource Management:

Do's:

- Conserve water to reduce the amount of wastewater that must be treated and disposed of by your system. Doing laundry over several days will put less stress on your system.
- Repair any leaking faucets or toilets. To detect toilet leaks, add several drops of food dye to the toilet tank and see if dye ends up in the bowl.
- Divert down spouts and other surface water away from your drainfield. Excessive water keeps the soil from adequately cleansing the wastewater.
- Have your septic tank inspected yearly and pumped regularly by a licensed septic tank contractor.

Don'ts:

- Don't drive over your drainfield or compact the soil in any way.
- Don't dig in your drainfield or build anything over it, and don't cover it with a hard surface such as concrete or asphalt.
- Don't plant anything over or near the drainfield except grass. Roots from nearby trees and shrubs may clog and damage the drain lines.
- Don't use your toilet as a trash can or poison your system and the groundwater by pouring harmful chemicals and cleansers down the drain. Harsh chemicals can kill the bacteria that help purify your wastewater.

For additional information on how septic systems work and how to properly plan a septic system, please visit the DHEC Environmental Health Onsite Wastewater page at the following link: http://www.scdhec.gov/health/envhlth/onsite_wastewater/septic_tank.htm

6.1.7 Urban Runoff

Urban runoff is surface runoff of rainwater created by urbanization outside of regulated areas which may pick up and carry pollutants to receiving waters. Pavement, compacted areas, roofs, reduced tree canopy and open space increase runoff volumes that rapidly flow into receiving waters. This increase in volume and velocity of runoff often causes stream bank erosion, channel incision and

sediment deposition in stream channels. In addition, runoff from these developed areas can increase stream temperatures that along with the increase in flow rate and pollutant loads negatively affect water quality and aquatic life (USEPA 2005). This runoff can pick up FC bacteria along the way. Many strategies currently exist to reduce FC loading from urban runoff and the USEPA nonpoint source pollution website provides extensive resources on this subject which can be accessed online at: <http://www.epa.gov/nps/urban.html>.

Some examples of urban nonpoint source bmps are street sweeping, stormwater wetlands, pet waste receptacles (equipped with waste bags), and educational signs which can be installed adjacent to receiving waters in the watershed such as parks, common areas, apartment complexes, trails, etc. Low impact development (LID) may also be effective. LID is an approach to land development (or re-development) that works with nature to manage stormwater as close to its source as possible. LID employs principles such as preserving and recreating natural landscape features, minimizing effective imperviousness to create functional and appealing site drainage that treat stormwater as a resource rather than a waste product. There are many practices that have been used to adhere to these principles such as bioretention facilities, rain gardens, vegetated rooftops, rain barrels, and permeable pavements (USEPA, 2009).

Some additional urban BMPs that can be adopted in public parks are doggy doileys and pooch patches. Doggy doileys are disposal units, which act like septic systems for pet wastes, and are installed in the ground where decomposition can occur (USEPA, 2001). This requires the pet owner to place the waste into the disposal units. Although the North Fork Edisto watershed is rural in nature, many of the urban runoff practices discussed in this section can be applied to individual households in the watershed. Education should be provided to individual homeowners in the referenced watershed on the contributions to FC loading from pet waste. Education to homeowners in the watershed on the fate of substances poured into storm drain inlets should also be provided. For additional information on urban runoff please see the SCDHEC Nonpoint Source Runoff Pollution homepage at <http://www.scdhec.gov/environment/water/npspage.htm>.

Clemson Extension's Home-A-Syst handbook can also help homeowners reduce sources of NPS pollution on their property. This document guides homeowners through a self-assessment of their property and can be accessed online at: <http://www.clemson.edu/waterquality/HOMASYS.HTM>

7.0 RESOURCES FOR POLLUTION MANAGEMENT

This section provides a listing of available resources to aid in the mitigation and control of pollutants. There are examples from across the nation, most of which are easily accessible on the world wide web.

7.1 General for Urban and Suburban Stormwater Mitigation

- National Management Measures to Control Nonpoint Source Pollution from Urban Areas – Draft. 2002. EPA842-B-02-003. Available at: <http://www.epa.gov/owow/nps/urbanmmm/index.html>
- Stormwater Management Volume Two: Stormwater Technical Manual. Massachusetts Department of Environmental Management. 1997. Available at: <http://www.mass.gov/dep/brp/stormwtr/stormpub.htm>
- Fact Sheets for the six minimum control measures for storm sewers regulated under Phase I or Phase II. Available at: http://cfpub1.epa.gov/npdes/stormwater/swfinal.cfm?program_id=6
- A Current Assessment of Urban Best Management Practices. 1992. Metropolitan Washington Council of Governments. Washington, DC
- Controlling Urban Runoff: A Practical Manual for Planning and Designing Urban BMPs. 1987. Metropolitan Washington Council of Governments. Washington, DC
- 2004 Stormwater Quality Manual. Connecticut Department of Environmental Protection 2004. Available at: <http://dep.state.ct.us/wtr/stormwater/strmwtrman.htm>
- Stormwater Treatment BMP New Technology Report. California Department of Transportation. 2004. SW-04-069-.04.02 Available at: http://www.dot.ca.gov/hq/env/stormwater/special/newsetup/pdfs/new_technology/CTSW-RT-04-069.pdf
- Moonlight Beach Urban Runoff Treatment facility: Using Ultraviolet Disinfection to Reduce Bacteria Counts. Rasmus, J. and K. Weldon. 2003. StormWater, May/June 2003. Available at http://www.forester.net/sw_0305_moonlight.html
- Operation, Maintenance, and Management of Stormwater Management Systems. Livingston, Shaver, Skupien, and Horner. August 1997. Watershed Management Institute. Call: (850) 926-5310.
- Model Ordinances to Protect Local Resources – Stormwater Control Operation and Maintenance. USEPA Webpage: <http://www.epa.gov/owow/nps/ordinance/stormwater.htm>
- Stormwater O & M Fact Sheet Preventive Maintenance. USEPA 1999. 832-F-99-004. Available at: <http://www.epa.gov/owm/mtb/prevmain.pdf>
- The MassHighway Stormwater Handbook. Massachusetts Highway Department. 2004. Available at: <http://166.90.180.162/mhd/downloads/projDev/swbook.pdf>
- University of New Hampshire Stormwater Center: Dedicated to the protection of water resources through effective stormwater management. Available at: <http://www.unh.edu/erg/cstev/index.htm#>

- EPA's Stormwater website: <http://www.epa.gov/region1/topics/water/stormwater.html>

7.2 Illicit Discharges

- Illicit Discharge Detection and Elimination Manual - A Handbook for Municipalities. 2003. New England Interstate Water Pollution Control Commission. Available at: http://www.neiwpcc.org/PDF_Docs/iddmanual.pdf
- Model Ordinances to Protect Local Resources – Illicit Discharges. USEPA webpage: <http://www.epa.gov/owow/nps/ordinance/discharges.htm>

7.3 Pet Waste

- National Management Measure to Control Non Point Source Pollution from Urban Areas – Draft. USEPA 2002. EPA 842-B-02-2003. Available from: <http://www.epa.gov/owow/nps/urbanmm/index.html>
- Septic Systems for Dogs? Nonpoint Source News-Notes 63. Pet Waste: Dealing with a Real Problem in Suburbia. Kemper, J. 2000. New Jersey Department of Environmental Protection. Available from: http://www.state.nj.us/dep/watershedmgmt/pet_waste_fredk.htm
- Stormwater Manager's Resource Center. Schueler, T., Center for Watershed Protection, Inc. <http://www.stormwatercenter.net>
- Guidance Specifying Management Measures for Sources of Nonpoint Pollution in Coastal Waters. U.S. EPA, Office of Water 1993. Washington, DC.
- National Menu of Best Management Practices for Stormwater Phase II. USEPA. 2002. Available at: <http://www.epa.gov/npdes/menuofbmps/menu.htm>
- Welcome to NVRC'S Four Mile Run Program. NVRC 2001. Available at: <http://www.novaregion.org/fourmilerun.htm>
- Boston's ordinance on dog waste. City of Boston Municipal Codes, Chapter XVI. 16-1.10A Dog Fouling. Available at: http://www.amlegal.com/boston_ma/
- Pet Waste and Water Quality. Hill, J.A., and D. Johnson. 1994. University of Wisconsin Extension Service. <http://cecommerce.uwex.edu/pdfs/GWQ006.PDF>
- Long Island Sound Study. Pet Waste Poster. EPA. Available at: <http://www.longislandsoundstudy.net/pubs/misc/pet.html>
- Source Water Protection Practices Bulletin: Managing Pet and Wildlife Waste to Prevent Contamination of Drinking Water. USEPA. 2001. EPA 916-F-01-027. Available at: <http://www.epa.gov/safewater/protect/pdfs/petwaste.pdf>

7.4 Wildlife

- An example of a bylaw prohibiting the feeding of wildlife: Prohibiting Feeding of Wildlife. Town of Bourne Bylaws Section 3.4.3. Available at: http://www.townofbourne.com/Town%20Offices/Bylaws/chapter_3.htm
- Integrated Management of Urban Canadian Geese. M Underhill. 1999. Conference Proceedings, Waterfowl Information Network.
- Urban Canadian Geese in Missouri. Missouri Conservationist Online. Available at: <http://www.conservation.state.mo.us/conmag/2004/02/20.htm>

7.5 Septic Systems

- National Management Measures to Control Nonpoint Source Pollution from Urban Areas – Draft. Chapter 6. New and Existing Onsite Wastewater Treatment Systems. USEPA 2002. EPA842-B-02-003. Available at: <http://www.epa.gov/owow/nps/urbanmmm/index.html>
- Septic Systems. USEPA Webpage: <http://cfpub.epa.gov/owm/septic/home.cfm>

7.6 Field Application of Manure

- Conservation Standard Practice-Irrigation Water Management. Number 449. United States Department of Agriculture (USDA) Natural Resources Conservation Service. 2003. Available at: <http://www.nrcs.usda.gov/technical/Standards/nhcp.html>
- Conservation Standard Practice-Filter Strip. Number 393. USDA Natural Resources Conservation Service (NRCS). 2003. Available at: <http://www.nrcs.usda.gov/technical/Standards/nhcp.html>
- Buffer Strips: Common Sense Conservation. USDA Natural Resource Conservation Service. No Date. Website. Available at: <http://www.nrcs.usda.gov/feature/buffers/>
- Conservation Standard Practice-Riparian Forest Buffer. Number 391. USDA Natural Resource Conservation Service. 2003. Available at: <http://www.nrcs.usda.gov/technical/Standards/nhcp.html>

7.7 Grazing Management

- Conservation Standard Practice-Stream Crossing. Number 578. USDA Natural Resource Conservation Service. 2003. Available at: <http://www.nrcs.usda.gov/technical/Standards/nhcp.html>

Guidance Specifying Management Measures for Nonpoint Source Pollution in Coastal Waters. Chapter 2. Management Measures for Agricultural Sources. Grazing Management. USEPA. Available at: <http://www.epa.gov/owow/nps/MMGI/Chapter2/ch2-2e.html>

7.8 Animal Feeding Operations and Barnyards

- National Management Measures to Control Nonpoint Source Pollution from Agriculture. USEPA 2003. Report: EPA 841-B-03-004. Available at: <http://www.epa.gov/owow/nps/agmm/index.html>
 - Livestock Manure Storage. Software designed to assess the threat to ground and surface water from manure storage facilities. USEPA. Available at: <http://www.epa.gov/seahome/manure.html>
 - National Engineering Handbook Part 651. Agricultural Waste Management Field Handbook. NRCS. Available At: <http://www.wcc.nrcs.usda.gov/awm/awmfh.html>
 - Animal Waste Management. NRCS website: <http://www.wcc.nrcs.usda.gov/awm/>
 - Animal Waste Management Software. A tool for estimating waste production and storage requirements. Available at: <http://www.wcc.nrcs.usda.gov/awm/awm.html>
 - Manure Management Planner. Software for creating manure management plans. Available at: <http://www.agry.purdue.edu/mmp/>
- Animal Feeding Operations Virtual Information Center. USEPA website:
- <http://cfpub.epa.gov/npdes/afo/virtualcenter.cfm>

7.9 Federal Agriculture Resources: Program Overviews, Technical Assistance, and Funding

- USDA-NRCS assists landowners with planning for the conservation of soil, water, and natural resources. Local, state, and federal agencies and policymakers also rely on NRCS expertise. Cost shares and financial incentives are available in some cases. Most work is done with local partners. The NRCS is the largest funding source for agricultural improvements. To find out about potential funding, see: <http://www.ma.nrcs.usda.gov/programs/>. To pursue obtaining funding, contact a local NRCS coordinator. Contact information is available at: http://www.ma.nrcs.usda.gov/contact/employee_directory.html
- NRCS provides a wealth of information and BMP fact sheets tailored to agricultural and conservation practices through the NRCS Electronic Field Office Technical Guide at: http://efotg.nrcs.usda.gov/efotg_locator.aspx?map=SC

The 2002 USDA Farm Bill (<http://www.nrcs.usda.gov/programs/farmbill/2002/>) provides a variety of programs related to conservation. Information can be found at: <http://www.nrcs.usda.gov/programs/farmbill/2002/products.html>. The following programs can be linked to from the USDA Farm Bill website:

Conservation Security Program (CSP): <http://www.nrcs.usda.gov/programs/csp/>

Conservation Reserve Program (CRP): <http://www.nrcs.usda.gov/programs/crp/>

Wetlands Reserve Program (WRP): <http://www.nrcs.usda.gov/programs/wrp/>

Environmental Quality Incentives Program (EQIP):

<http://www.nrcs.usda.gov/programs/eqip/>

Grassland Reserve Program (GRP): <http://www.nrcs.usda.gov/programs/GRP/>

Conservation of Private Grazing Land Program (CPGL):

<http://www.nrcs.usda.gov/programs/cpgl/>

Wildlife Habitat Incentives Program (WHIP): <http://www.nrcs.usda.gov/programs/whip/>

Farm and Ranch Land Protection Program (FRPP):

<http://www.nrcs.usda.gov/programs/frpp/>

Resource Conservation and Development Program (RC&D):

<http://www.nrcs.usda.gov/programs/rcd/>

- CORE4 Conservation Practices. The common sense approach to natural resource conservation. USDA-NRCS (1999). This manual is intended to help USDA-NRCS personnel and other conservation and nonpoint source management professionals implement effective programs using four core conservation practices: conservation tillage, nutrient management, pest management, and conservation buffers, available at: <http://www.nrcs.usda.gov/technical/ECS/agronomy/core4.pdf>
- County soil survey maps are available from NRCS at: <http://soils.usda.gov>
- Guidance Specifying Management Measures for Sources of Nonpoint Pollution in Coastal Waters. U.S. EPA, Office of Water (1993). Developed for use by State Coastal Nonpoint Pollution Control Programs, Chapter 2 of this document covers erosion control, animal feeding operation management, grazing practices, and management of nutrients, pesticides, and irrigation water, available at: <http://www.epa.gov/owow/nps/MMGI/Chapter2/index.html>.
- Farm-A-Syst is a partnership between government agencies and private business that enables landowners to prevent pollution on farms, ranches, and in homes using confidential environmental assessments, available at: <http://www.uwex.edu/farmasyst/>
- State Environmental Laws Affecting South Carolina Agriculture: A comprehensive assessment of regulatory issues related to South Carolina agriculture has been compiled by the National Association of State Departments, available at: <http://www.nasda-hq.org/nasda/nasda/Foundation/state/states.htm>

- Waterborne Pathogens in Agricultural Wastewater. Rosen, B.H., 2000. USDA, NRCS, Watershed Science Institute. Available at: ftp://ftp-fc.sc.egov.usda.gov/WSI/pdffiles/Pathogens_in_Agricultural_Watersheds.pdf
- Stormwater Program (Phase II); Municipal Sewer Systems and Construction Sites, 64 Federal Register 235 (8 December 1999), pp. 68837.
- Water Quality Planning and Management, Title 40 Code of Federal Regulations, Pt. 130.2(i). 2006 ed.

8.0 REFERENCES AND BIBLIOGRAPHY

- American Society of Agricultural Engineers (ASAE). 1998. ASAE Standards, 45th edition. D384.1 DEC93.
Manure production and characteristics St. Joseph, Mich.
- Ayres Associates 1993. Onsite Sewage Disposal Systems Research in Florida. The Capacity of Fine Sandy Soil for Septic Tank Effluent Treatment: A Field Investigation at an In-Situ Lysimeter Facility in Florida.
- Bonta, J.V. and B. Cleland. 2003. Incorporating Natural Variability, Uncertainty, and Risk into Water Quality Evaluations Using Duration Curves. *Journal of American Water Resource Association* 39(12):1481-1496
- Gaffield, S. J., R. L. Goo, L.A. Richards, and R. J. Jackson. 2003. Public Health Effects of Inadequately Managed Stormwater. in Runoff. *American Journal of Public Health* 93(9): 1527-1533. September 2003.
- Metcalf and Eddy 1991. Wastewater Engineering: Treatment, Disposal, Reuse. Third Edition.
- National Land Cover Data Set (NLCD). 2001. Nation-wide Landsat-7 Imagery 1999. Available through the Multi-Resolution Land Characteristics (MRLC) Consortium. <http://www.mrlc.gov/>
- SCDHEC. 1998. Implementation Plan for Achieving Total Maximum Daily Load Reductions from Nonpoint Sources for the State of South Carolina.
- SCDHEC. 2002. Standards for the Permitting of Agricultural Animal Facilities (Regulation 61-43). Bureau of Water. Columbia, SC
- SCDHEC. 2003. Water Pollution Control Permits (Regulation 61-9) Office of Environmental Quality Control, Columbia, SC.
- United States Department of Agriculture (USDA). 2008. National Agriculture Statistics Service. 2002 Census of Agriculture. Available at: <http://www.nass.usda.gov/census/census02/volume1/sc/index2.htm>
- United States Environmental Protection Agency (USEPA). 1983. Final Report of the Nationwide Urban Runoff Program, Vol 1. Water Planning Division, US Environmental Protection Agency, Washington, DC.
- United States Environmental Protection Agency (USEPA). 1991. Guidance for Water Quality-Based Decisions: The TMDL Process. Office of Water, EPA 440/4-91-001.


United States Environmental Protection Agency (USEPA). 2001. Protocol for Developing Pathogen TMDLs. First Edition. Office of Water, EPA 841-R-00-002.

US Geological Survey. 2007. Water-Resources Real-time Data South Carolina Water Year. United States Geological Survey. Available at <http://waterdata.usgs.gov/nw>


Appendix A

Additional Rain Charts By Station


Precipitation and Fecal Coliform Data by Date- Impaired Site E-007B




Precipitation and Fecal Coliform Data by Date- Impaired Site E-008



Precipitation and Fecal Coliform Data by Date- Impaired Site E-092




Precipitation and Fecal Coliform Data by Date- Impaired Site E-099




Appendix B

Additional Load Duration Curve Graphs by Station


Load Duration Curve for North Fork Edisto Station E-092




Load Duration Curve for North Fork Edisto Station E-007B



Load Duration Curve for North Fork Edisto Station E-008



Load Duration Curve for North Fork Edisto Station E-099



Appendix C- Data Tables

90th Percentile Fecal Coliform Concentrations (#/100 mL)						
Hydro Categ Range	High Flow 0-10	Moist Cond. 10-40	Mid Range 40-60	Dry Flow 60-90	Low Flow 90-100	Samples
E-035	48	270	294	1094	1334	36

Mid Point Hydrologic Category Flow (cfs)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-035	960.00	545.60	394.40	284.60	182.04

Existing Load (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-035	1.13E+12	3.60E+12	2.84E+12	7.62E+12	5.94E+12

Target Load (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-035	9.39E+12	5.34E+12	3.86E+12	2.65E+12	1.69E+12

Load Reduction Necessary (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-035	N/A	N/A	N/A	4.97E+12	N/A

% Load Reduction Necessary					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-035	N/A	71	N/A	N/A	N/A

90th Percentile Fecal Coliform Concentrations (#/100 mL)						
Hydro Categ Range	High Flow 0-10	Moist Cond. 10-40	Mid Range 40-60	Dry Flow 60-90	Low Flow 90-100	Samples
E-092	329	260	276	400	162	47

Mid Point Hydrologic Category Flow (cfs)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-092	1286.09	730.93	528.37	381.27	243.87

Existing Load (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-092	1.04E+12	4.65E+12	3.57E+12	3.73E+12	9.67E+11

Target Load (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-092	1.20E+13	6.80E+12	4.91E+12	3.54E+12	2.27E+12

Load Reduction Necessary (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-092	N/A	N/A	N/A	0.19E+12	N/A

% Load Reduction Necessary					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-092	N/A	N/A	N/A	5	N/A

90th Percentile Fecal Coliform Concentrations (#/100 mL)						
Hydro Categ Range	High Flow 0-10	Moist Cond. 10-40	Mid Range 40-60	Dry Flow 60-90	Low Flow 90-100	Samples
E-007B	440	540	215	276	192	47

Mid Point Hydrologic Category Flow (cfs)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-007B	1286.09	730.93	528.37	381.27	243.87

Existing Load (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-007B	1.38E+13	9.66E+12	2.78E+12	2.57E+12	1.15E+12

Target Load (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-007B	1.20E+13	6.80E+12	4.91E+12	3.54E+12	2.27E+12

Load Reduction Necessary (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-007B	N/A	2.86E+12	N/A	N/A	N/A

% Load Reduction Necessary					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-007B	N/A	30	N/A	N/A	N/A

90th Percentile Fecal Coliform Concentrations (#/100 mL)						
Hydro Categ Range	High Flow 0-10	Moist Cond. 10-40	Mid Range 40-60	Dry Flow 60-90	Low Flow 90-100	Samples
E-008	76	468	176	258	72	47

Mid Point Hydrologic Category Flow (cfs)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-008	1268.09	730.93	528.37	381.27	243.87

Existing Load (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-008	2.39E+12	8.37E+12	2.28E+12	2.41E+12	4.30E+11

Target Load (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-008	1.25E+13	6.80E+12	4.91E+12	3.54E+12	2.27E+12

Load Reduction Necessary (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-008	N/A	1.57E+12	N/A	N/A	N/A

% Load Reduction Necessary					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-008	N/A	19	N/A	N/A	N/A

90th Percentile Fecal Coliform Concentrations (#/100 mL)						
Hydro Categ Range	High Flow 0-10	Moist Cond. 10-40	Mid Range 40-60	Dry Flow 60-90	Low Flow 90-100	Samples
E-099	455	400	144	296	92	93

Mid Point Hydrologic Category Flow (cfs)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-099	1279.06	726.93	525.48	379.19	242.54

Existing Load (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-099	1.42E+13	7.11E+12	1.85E+12	2.25E+12	5.44E+11

Target Load (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-099	1.19E+13	6.76E+12	4.89E+12	3.53E+12	2.25E+12

Load Reduction Necessary (#/day)					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-099	N/A	0.35E+12	N/A	N/A	N/A

% Load Reduction Necessary					
Hydro Categ (Mid-Point)	High Flow (5)	Moist Cond. (25)	Mid Range (50)	Dry (75)	Low Flow (95)
E-099	N/A	5	N/A	N/A	N/A

Appendix D

Fecal Coliform Water Quality Data Summary for Impaired Station E-035 By Date

Date	Result
05/26/99	48
06/15/99	140
07/27/99	110
08/03/99	67
09/28/99	310
10/26/99	220
05/16/00	90
06/05/00	120
07/05/00	260
08/10/00	130
09/12/00	110
10/05/00	110
01/02/01	24
02/28/01	79
03/19/01	30
04/10/01	240
05/07/01	100
06/18/01	130
07/19/01	120
08/29/01	420
09/04/01	300
10/09/01	240
11/29/01	110
12/12/01	290
01/31/06	20
02/27/06	17
03/22/06	160
04/17/06	320
05/03/06	100
06/14/06	2900
07/13/06	120
08/30/06	270
09/13/06	1600
10/11/06	110
11/08/06	52
12/06/06	53

Fecal Coliform Water Quality Data Summary for Impaired Station E-092 By Date

Date	Result
01/04/99	260
02/01/99	230
03/24/99	55
04/01/99	110
05/03/99	340
06/01/99	110
07/29/99	200
08/19/99	110
09/08/99	82
10/12/99	80
11/04/99	340
12/02/99	120
01/10/00	400
02/07/00	92
03/09/00	58
04/11/00	78
05/08/00	150
06/08/00	180
07/13/00	0
08/02/00	400
09/19/00	240
10/10/00	60
11/06/00	180
12/05/00	120
01/22/01	240
02/15/01	200
03/12/01	58
04/10/01	70
06/28/01	78
07/17/01	70
08/06/01	160
09/04/01	140
10/22/01	120
11/19/01	70
12/05/01	88
01/11/06	67
02/23/06	210
03/08/06	40
04/12/06	46
05/24/06	210
06/20/06	35
07/27/06	480

08/21/06	440
09/20/06	540
10/12/06	320
11/07/06	400
12/11/06	86

Fecal Coliform Water Quality Data Summary for Impaired Station E-007B By Date

Date	Result
01/04/99	220
02/01/99	190
03/09/99	0
04/01/99	0
05/20/99	40
06/17/99	76
07/28/99	29
08/12/99	100
09/23/99	100
10/13/99	90
11/04/99	430
12/02/99	50
01/10/00	150
02/07/00	100
03/09/00	45
04/11/00	0
05/09/00	440
06/15/00	140
07/20/00	120
08/17/00	32
09/14/00	75
10/26/00	370
11/01/00	65
12/05/00	80
01/11/01	40
02/08/01	110
03/22/01	170
04/19/01	83
06/14/01	160
07/12/01	620
08/21/01	70
09/20/01	480
10/11/01	330
11/29/01	50

12/13/01	430
01/17/06	70
02/27/06	480
03/08/06	50
04/11/06	170
05/23/06	83
06/13/06	330
07/20/06	40
08/03/06	110
09/21/06	160
11/01/06	620
12/14/06	29

Fecal Coliform Water Quality Data Summary for Impaired Station E-008 By Date

Date	Result
01/04/99	340
02/01/99	76
03/09/99	140
04/06/99	120
05/20/99	260
06/17/99	120
07/28/99	60
08/12/99	150
09/23/99	180
10/13/99	300
11/04/99	100
12/02/99	140
01/10/00	980
02/07/00	0
03/09/00	100
04/11/00	130
05/09/00	0
06/15/00	85
07/20/00	20
08/17/00	74
09/14/00	50
10/26/00	75
11/01/00	36
12/05/00	85
01/11/01	30
02/08/01	82
03/22/01	60
04/19/01	94

06/14/01	0
07/12/01	44
08/21/01	75
09/20/01	50
10/11/01	48
11/29/01	48
12/13/01	72
01/17/06	140
02/27/06	45
03/08/06	78
04/11/06	240
05/23/06	65
06/13/06	50
07/20/06	55
09/21/06	62
10/16/06	45
12/14/06	40

Fecal Coliform Water Quality Data Summary for Impaired Station E-099 By Date

Date	Result
-------------	---------------

1/4/1999	280
2/1/1999	410
3/9/1999	340
4/5/1999	100
5/3/1999	270
6/1/1999	40
7/1/1999	240
8/19/1999	280
9/8/1999	590
10/12/1999	360
11/4/1999	260
12/2/1999	140
2/7/2000	100
3/9/2000	88
4/11/2000	45
5/8/2000	78
6/8/2000	110
7/13/2000	70
8/2/2000	120
9/19/2000	70
10/10/2000	45
11/6/2000	100
12/5/2000	76
1/18/2001	100

2/5/2001	65
3/12/2001	45
4/10/2001	76
8/2/2001	110
9/11/2001	150
10/3/2001	48
11/13/2001	66
12/10/2001	120
1/9/2002	480
2/4/2002	55
3/4/2002	440
4/4/2002	120
5/15/2002	42
6/4/2002	20
7/8/2002	75
8/12/2002	60
9/4/2002	54
10/1/2002	30
11/6/2002	160
12/11/2002	38
1/8/2003	42
2/5/2003	44
3/4/2003	32
4/1/2003	14
5/7/2003	320
6/4/2003	160
7/17/2003	80
8/6/2003	140
9/2/2003	180
10/28/2003	120
11/4/2003	100
12/1/2003	44
1/7/2004	46
2/4/2004	52
3/3/2004	38
4/7/2004	26
5/11/2004	20
6/2/2004	60
7/20/2004	140
9/9/2004	760
10/5/2004	90
11/8/2004	260
12/13/2004	100
1/20/2005	180
2/2/2005	58
3/8/2005	30
4/27/2005	24
5/17/2005	98

6/7/2005	440
7/5/2005	500
8/1/2005	200
9/6/2005	100
10/4/2005	100
11/1/2005	48
12/1/2005	120
1/10/2006	120
2/7/2006	87
3/7/2006	30
4/11/2006	34
5/3/2006	260
7/10/2006	20
8/2/2006	62
9/7/2006	460
10/17/2006	240
11/2/2006	540
12/5/2006	100
1/4/2007	62
2/7/2007	210
3/6/2007	64
4/12/2007	160
5/16/2007	99
6/13/2007	160
7/11/2007	200
8/21/2007	200
9/11/2007	160
10/23/2007	110
11/28/2007	60
12/6/2007	50
1/16/2008	93
2/13/2008	68
3/5/2008	80
4/9/2008	240
5/1/2008	120
6/24/2008	250
7/9/2008	1700
8/19/2008	350
9/10/2008	110
10/9/2008	2300
11/13/2008	10
12/9/2008	55

Appendix E

Watershed Photos



Impaired Site E-035 Bull Swamp Creek




Impaired Site E-092, Hwy 3 going across



Impaired Site E-092 boat ramp



Near impaired site E-007B, waterfowl present



Near impaired site E-008, thick forested area



E-008

Appendix F. Evaluating the Progress of MS4 Programs:

Meeting the Goals of TMDLs and Attaining Water Quality Standards

August 2008

Described below are potential approaches that may be used by MS4 permit holders. These are recommendations and examples only, as SCDHEC-BOW recognizes that other approaches may be utilized or employed to meet compliance goals.

1. Calculate pollutant load reduction for each best management practice (BMP) deployed:
 - Retrofitting stormwater outlets
 - Creation of green space
 - LID activities (e.g., creation of porous pavements)
 - Creations of riparian buffers
 - Stream bank restoration
 - Scoop the poop program (how many pounds of poop were scooped/collected)
 - Street sweeping program (amount of materials collected etc.)
 - Construction & post-construction site runoff controls
2. Description & documentation of programs directed towards reducing pollutant loading
 - Document tangible efforts made to reduce impacts to urban runoff
 - Track type and number of structural BMPs installed
 - Parking lot maintenance program for pollutant load reduction
 - Identification and elimination of illicit discharges
 - Zoning changes and ordinances designed to reduce pollutant loading
 - Modeling of activities & programs for reducing pollutant reductions
3. Description & documentation of social indicators, outreach, and education programs
 - Number/Type of training & education activities conducted and survey results
 - Activities conducted to increase awareness and knowledge – residents, business owners. What changes have been made based on these efforts? Any measured behavior or knowledge changes?
 - Participation in stream and/or lake clean-up events or activities
 - Number of environmental action pledges
4. Water quality monitoring: A direct and effective way to evaluate the effectiveness of stormwater management plan activities.
 - Use of data collected from existing monitoring activities (e.g., SCDHEC data for ambient monitoring program available through STORET; water supply intake testing; voluntary watershed group's monitoring, etc)
 - Establish a monitoring program for permitted outfalls and/or waterbodies within MS4 areas as deemed necessary– use a certified lab

- Monitoring should focus on water quality parameters and locations that would both link pollutant sources and BMPs being implemented

5. Links:

- Evaluating the Effectiveness of Municipal Stormwater Programs. September 2007. EPA 833-F-07-010
- The BMP database - <http://www.bmpdatabase.org/BMPPerformance.htm> (this link is specifically to the BMP performance page, and lot more)
- EPA's STORET data warehouse - http://www.epa.gov/storet/dw_home.html
- EPA Region 5: STEPL – Spreadsheet tool for estimating pollutant loads <http://it.tetrattech-ffx.com/stepl/>
- Measurable goals guidance for Phase II Small MS4 - <http://cfpub.epa.gov/npdes/stormwater/measurablegoals/index.cfm>
- Environmental indicators for stormwater program- <http://cfpub.epa.gov/npdes/stormwater/measurablegoals/part5.cfm>
- National menu of stormwater best management practices (BMPs) - <http://cfpub.epa.gov/npdes/stormwater/menuofbmps/index.cfm>
- SCDHEC – BOW: 319 grant program has attempted to calculate the load reductions for the following BMPs:
 - Septic tank repair or replacement
 - Removing livestock from streams (cattle, horses, mules)
 - Livestock fencing
 - Waste Storage Facilities (aka stacking sheds)
 - Strip cropping
 - Prescribed grazing
 - Critical Area Planting
 - Runoff Management System
 - Waste Management System
 - Solids Separation Basin
 - Riparian Buffers